



Project: _____
 Location: _____
 Cat. #: _____
 Type: _____
 Quantity: _____

LED

EMEW | Wet Location Exit/Emergency Combo

Features:

- Energy efficient, long life red or green LED exit sign illumination
- Ultra-bright, long life white LED lamp heads
- 3 LEDs per head (3.6 watt total per head)
- Adjustable LED lamp heads allow for optimal center to center spacing.
- Dual 120/277V
- Bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery)
- 6V long life, maintenance free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Easy snap-out chevron directional indicators

Construction:

- 5VA flame retardant, UV stabilized polycarbonate housing in white, black or gray finish
- High-impact resistant, UV stabilized polycarbonate clear lens
- Corrosion resistant enclosure with engineering grade silicone gasket
- Knockout's provided for conduit feed applications

Certifications:

- UL listed for wet locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes
- Certified to CEC under Title 20 Regulations



Mounting:

- Die-cast aluminum mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

Ambient operating Temp.:

- 0°C to 50°C
- -20°C to 50°C with CW option

Warranty:

- 5 year limited warranty on housing and electronics. Battery prorated for 5 yrs.
- see www.LumenFocus.com for complete warranty terms and conditions



Ordering Guide:

example: EMEW 2 R DV W-SD CW

Series	# of Faces	Letter Color	Voltage	Housing Color	-	Options
EMEW			DV		-	
EMEW Wet Location Exit/ Emergency Combo	1 Single Face 2 Universal Single/ Double Face	R Red G Green	DV Dual 120/277V	W White B Black G Gray		Blank None RC Remote Capacity (Maximum 7.2W Allowed) SD Self Diagnostics TP Tamper-Proof Hardware CW Cold Weather - Internal Heater and Battery Blanket (-20°C to 50°C)

Schematic:

