

IES ROAD REPORT

PHOTOMETRIC FILENAME : ADS SEL 5S UV FPC 7SEL_35W-5000K.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] 20201113(s)
 [TESTLAB] Dongguan New Testing Centre Co., Ltd
 [TESTDATE] 13 November 2020
 [ISSUEDATE] 2020-11-16 13:34:07
 [NEARFIELD]
 [LAMPPOSITION] 0,0
 [OTHER] EVERFINE GO-R5000_V2 SYSTEM
 [MANUFAC] LumenFocus, LLC.
 [LUMCAT] ADS SEL 5S UV FPC 7SEL
 [LUMINAIRE] DUSK TO DAWN AREA LIGHT SELECT (35W-5000K)
 [BALLAST] 120-277Vac 50/60Hz
 [OTHER]

[OTHER]	Gamma(deg)	Fz(lm)	Ft(lm)	%Lum	%Lamp
[OTHER]	0- 10	205.22	205.22	2.54	2.54
[OTHER]	10- 20	625.68	830.90	10.29	10.29
[OTHER]	20- 30	1033.28	1864.18	23.09	23.09
[OTHER]	30- 40	1398.45	3262.63	40.41	40.41
[OTHER]	40- 50	1672.20	4934.82	61.12	61.12
[OTHER]	50- 60	1617.33	6552.15	81.15	81.15
[OTHER]	60- 70	1011.77	7563.92	93.68	93.68
[OTHER]	70- 80	370.68	7934.61	98.27	98.27
[OTHER]	80- 90	106.72	8041.33	99.59	99.59
[OTHER]	90-100	13.83	8055.16	99.76	99.76
[OTHER]	100-110	7.70	8062.86	99.85	99.85
[OTHER]	110-120	3.93	8066.79	99.90	99.90
[OTHER]	120-130	2.79	8069.58	99.94	99.94
[OTHER]	130-140	1.77	8071.35	99.96	99.96
[OTHER]	140-150	1.31	8072.66	99.98	99.98
[OTHER]	150-160	1.05	8073.71	99.99	99.99
[OTHER]	160-170	0.67	8074.37	100.00	100.00
[OTHER]	170-180	0.23	8074.60	100.00	100.00
[OTHER]					


IES ROAD REPORT**PHOTOMETRIC FILENAME : ADS SEL 5S UV FPC 7SEL_35W-5000K.IES****CHARACTERISTICS**

IES Classification	Type VS
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4691
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	134
Total Luminaire Watts	35
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	1369.811
Maximum Candela Angle	300H 37V
Maximum Candela (<90 Degrees Vertical)	1369.811
Maximum Candela Angle (<90 Degrees Vertical)	300H 37V
Maximum Candela At 90 Degrees Vertical	25.938 (0.6% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	141.844 (3.0% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	541.4	N.A.	11.5
FM - Front-Medium (30-60)	1367.1	N.A.	29.1
FH - Front-High (60-80)	415.8	N.A.	8.9
FVH - Front-Very High (80-90)	32.5	N.A.	0.7
BL - Back-Low (0-30)	541.6	N.A.	11.5
BM - Back-Medium (30-60)	1356.4	N.A.	28.9
BH - Back-High (60-80)	387.4	N.A.	8.3
BVH - Back-Very High (80-90)	29.5	N.A.	0.6
UL - Uplight-Low (90-100)	8.0	N.A.	0.2
UH - Uplight-High (100-180)	11.3	N.A.	0.2
Total	4691.0	N.A.	100.0
BUG Rating	B2-U2-G1		

COEFFICIENTS OF UTILIZATION




FLUX DISTRIBUTION

	Lumens	Percent Of Luminaire
Downward Street Side	2356.7	50.2
Downward House Side	2314.9	49.3
Downward Total	4671.6	99.6
Upward Street Side	9.4	0.2
Upward House Side	9.9	0.2
Upward Total	19.3	0.4
Total Flux	4690.9	100.0

IES ROAD REPORT

PHOTOMETRIC FILENAME : ADS SEL 5S UV FPC 7SEL_35W-5000K.IES

POLAR GRAPH




Maximum Candela = 1369.811 Located At Horizontal Angle = 300, Vertical Angle = 37


1 - Vertical Plane Through Horizontal Angles (300 - 120) (Through Max. Cd.)

2 - Horizontal Cone Through Vertical Angle (37) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=541.4, Medium=1367.1, High=415.8, Very High=32.5
Back: Low=541.6, Medium=1356.4, High=387.4, Very High=29.5
Uplight: Low=8.0, High=11.3

BUG Rating : B2-U2-G1