



IES INDOOR REPORT

PHOTOMETRIC FILENAME : FFR G2 14 MD UV FA 930.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001588-017 (s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 2/17/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] FFR G2 14 MD UV FA 930

[LUMINAIRE] Retrofit kit installed in an A.L.P. EF-1x4-2L-23GA 1x4 housing,

[MORE] formed white painted steel reflectors, frosted linear ribbed plastic enclosure.

[LAMP] 96 white LEDs, two LS3873A7_3000_90R 3000K LED boards

[BALLAST] One ULT D10CC30UNVPW-C LED driver programmed at 660mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4745
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	141
Total Luminaire Watts	33.7
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	3.75 ft
Luminous Width (90-270)	0.75 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	5650	6066	6447
55	5223	5793	6121
65	4709	5261	5418
75	3956	4295	4073
85	2607	1564	799

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFR G2 14 MD UV FA 930.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	638.47	N.A.	13.50
0-30	1347.56	N.A.	28.40
0-40	2191.49	N.A.	46.20
0-60	3823.29	N.A.	80.60
0-80	4688.16	N.A.	98.80
0-90	4744.65	N.A.	100.00
10-90	4578.77	N.A.	96.50
20-40	1553.02	N.A.	32.70
20-50	2417.32	N.A.	50.90
40-70	2196.95	N.A.	46.30
60-80	864.87	N.A.	18.20
70-80	299.73	N.A.	6.30
80-90	56.49	N.A.	1.20
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	4744.65	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	165.88
10-20	472.59
20-30	709.09
30-40	843.93
40-50	864.30
50-60	767.50
60-70	565.15
70-80	299.73
80-90	56.49
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFR G2 14 MD UV FA 930.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	105	100	97	106	102	98	95	98	95	92	94	92	89	91	88	87	85
2	99	91	85	79	97	89	83	78	86	81	76	83	78	74	80	76	73	71
3	91	80	72	66	88	79	71	65	76	69	64	73	68	63	70	66	62	60
4	83	71	63	56	81	70	62	55	67	60	55	65	59	54	63	58	53	51
5	76	64	55	48	74	63	54	48	60	53	47	58	52	47	57	51	46	44
6	71	57	48	42	69	56	48	42	55	47	42	53	46	41	51	45	41	39
7	65	52	43	37	64	51	43	37	50	42	37	48	42	37	47	41	36	34
8	61	47	39	33	59	47	39	33	45	38	33	44	38	33	43	37	32	31
9	57	44	35	30	56	43	35	30	42	35	30	41	34	30	40	34	29	28
10	53	40	32	27	52	40	32	27	39	32	27	38	31	27	37	31	27	25

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFR G2 14 MD UV FA 930.IES

UGR TABLE - CORRECTED


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	17.7	19.4	18.1	19.7	20.0	18.6	20.2	18.9	20.5	20.8
	3H	19.4	20.9	19.8	21.2	21.6	20.2	21.7	20.6	22.0	22.4
	4H	20.1	21.4	20.5	21.8	22.2	20.7	22.1	21.1	22.4	22.8
	6H	20.5	21.8	20.9	22.1	22.5	21.0	22.3	21.4	22.6	23.0
	8H	20.6	21.8	21.0	22.2	22.6	21.0	22.2	21.5	22.6	23.0
	12H	20.7	21.8	21.1	22.2	22.6	21.0	22.2	21.4	22.6	23.0
4H	2H	18.5	19.8	18.9	20.2	20.6	19.1	20.5	19.5	20.9	21.2
	3H	20.4	21.5	20.8	21.9	22.3	21.0	22.1	21.4	22.5	22.9
	4H	21.1	22.2	21.6	22.6	23.0	21.6	22.6	22.0	23.1	23.5
	6H	21.7	22.6	22.1	23.0	23.5	22.0	22.9	22.4	23.3	23.8
	8H	21.8	22.7	22.3	23.1	23.6	22.0	22.9	22.5	23.3	23.8
	12H	21.9	22.7	22.4	23.1	23.6	22.0	22.8	22.5	23.3	23.7
8H	4H	21.4	22.3	21.9	22.7	23.2	21.8	22.7	22.3	23.1	23.6
	6H	22.1	22.8	22.6	23.3	23.7	22.3	23.0	22.8	23.5	24.0
	8H	22.3	22.9	22.8	23.4	23.9	22.4	23.0	22.9	23.5	24.0
	12H	22.4	23.0	22.9	23.5	24.0	22.4	22.9	22.9	23.4	24.0
12H	4H	21.4	22.2	21.9	22.7	23.1	21.9	22.6	22.3	23.1	23.6
	6H	22.1	22.7	22.6	23.2	23.7	22.3	23.0	22.8	23.4	24.0
	8H	22.3	22.9	22.8	23.4	23.9	22.4	23.0	22.9	23.5	24.0

Maximum UGR = 24.0

POLAR GRAPH



Maximum Candela = 1758.668 Located At Horizontal Angle = 90, Vertical Angle = 2
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (2) (Through Max. Cd.)