



IES INDOOR REPORT

PHOTOMETRIC FILENAME : FFR G2 24 SH UV FA 950.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001588-007A

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 2/17/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] FFR G2 24 SH UV FA 950

[LUMINAIRE] Retrofit kit installed in an A.L.P. EL-2x4-23-2 2x4 housing,

[MORE] formed white painted steel reflectors, frosted linear ribbed plastic enclosure.

[LAMP] 128 white LEDs, two LS3873A8_5000_90R 5000K 64 LED boards

[BALLAST] One ULT D21CC80UNVPW-C LED driver programmed at 1220mA

[OTHER] 120.0Vac, 60.00Hz, 0.5234A, 62.63W, 0.997PF, 5.9%THD(i)

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	8923
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	142
Total Luminaire Watts	62.631
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	3.75 ft
Luminous Width (90-270)	1.75 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4236	4612	4978
55	3891	4500	5103
65	3486	4467	5413
75	2925	4584	6053
85	1974	4024	4174

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFR G2 24 SH UV FA 950.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	1124.42	N.A.	12.60
0-30	2373.17	N.A.	26.60
0-40	3861.56	N.A.	43.30
0-60	6807.19	N.A.	76.30
0-80	8702.25	N.A.	97.50
0-90	8922.94	N.A.	100.00
10-90	8630.8	N.A.	96.70
20-40	2737.14	N.A.	30.70
20-50	4273.26	N.A.	47.90
40-70	4085.1	N.A.	45.80
60-80	1895.07	N.A.	21.20
70-80	755.60	N.A.	8.50
80-90	220.69	N.A.	2.50
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	8922.94	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	292.14
10-20	832.28
20-30	1248.75
30-40	1488.39
40-50	1536.12
50-60	1409.51
60-70	1139.47
70-80	755.60
80-90	220.69
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFR G2 24 SH UV FA 950.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	105	101	97	93	97	93	90	93	90	87	89	87	85	83
2	98	89	82	76	95	88	81	75	84	78	74	81	76	72	78	74	70	68
3	89	78	70	63	87	77	69	63	74	67	61	71	65	60	68	63	59	57
4	82	69	60	53	79	68	59	53	65	58	52	63	57	51	61	55	51	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	45	55	49	44	42
6	69	56	46	40	67	55	46	40	53	45	39	51	44	39	49	43	39	37
7	64	50	41	35	62	50	41	35	48	40	35	47	40	35	45	39	34	32
8	60	46	37	31	58	45	37	31	44	36	31	43	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	36	30	25	23

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFR G2 24 SH UV FA 950.IES

UGR TABLE - CORRECTED


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	16.5	18.1	16.8	18.5	18.8	18.1	19.8	18.5	20.1	20.4
	3H	18.2	19.7	18.6	20.0	20.4	20.5	22.0	20.9	22.3	22.7
	4H	18.8	20.3	19.2	20.6	21.0	21.5	23.0	21.9	23.3	23.7
	6H	19.3	20.6	19.7	21.0	21.4	22.5	23.8	22.9	24.2	24.5
	8H	19.4	20.7	19.8	21.1	21.5	22.8	24.0	23.2	24.4	24.8
	12H	19.5	20.7	19.9	21.1	21.5	22.9	24.1	23.3	24.5	24.9
4H	2H	17.4	18.8	17.8	19.2	19.5	18.7	20.1	19.1	20.4	20.8
	3H	19.4	20.6	19.8	21.0	21.4	21.3	22.5	21.7	22.9	23.3
	4H	20.1	21.2	20.6	21.6	22.1	22.5	23.6	23.0	24.0	24.5
	6H	20.7	21.7	21.2	22.1	22.6	23.6	24.6	24.1	25.0	25.5
	8H	20.9	21.8	21.4	22.2	22.7	24.0	24.9	24.5	25.3	25.8
	12H	21.0	21.8	21.5	22.3	22.8	24.2	25.0	24.7	25.5	26.0
8H	4H	20.8	21.7	21.3	22.1	22.6	22.8	23.7	23.3	24.2	24.6
	6H	21.6	22.3	22.0	22.8	23.3	24.1	24.9	24.6	25.4	25.8
	8H	21.8	22.5	22.3	23.0	23.5	24.6	25.2	25.1	25.8	26.2
	12H	22.0	22.6	22.5	23.1	23.7	24.9	25.5	25.4	26.0	26.5
12H	4H	20.9	21.7	21.4	22.2	22.7	22.9	23.7	23.3	24.2	24.6
	6H	21.8	22.5	22.3	22.9	23.4	24.2	24.9	24.7	25.3	25.9
	8H	22.1	22.7	22.6	23.2	23.8	24.7	25.3	25.2	25.8	26.3

Maximum UGR = 26.5

POLAR GRAPH



Maximum Candela = 3095 Located At Horizontal Angle = 90, Vertical Angle = 1.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (1.5) (Through Max. Cd.)