



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 935.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-013(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/2/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] ECL G2 2 MD UV FR 935

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMP] 28 white LEDs on one LS3872A LED board

[BALLAST] One ULT D700C20UNVPW-C LED driver labeled as 320mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2041
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	128
Total Luminaire Watts	16
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	1.99 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	8469	8250	8326
55	7268	7442	7648
65	5733	6460	6765
75	4071	5463	5756
85	2137	4974	5094

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 935.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	254.46	N.A.	12.50
0-30	540.96	N.A.	26.50
0-40	885.34	N.A.	43.40
0-60	1549.7	N.A.	75.90
0-80	1929.92	N.A.	94.50
0-90	2003.89	N.A.	98.20
10-90	1938.16	N.A.	94.90
20-40	630.88	N.A.	30.90
20-50	983.74	N.A.	48.20
40-70	898.34	N.A.	44.00
60-80	380.22	N.A.	18.60
70-80	146.24	N.A.	7.20
80-90	73.98	N.A.	3.60
90-110	37.36	N.A.	1.80
90-120	37.47	N.A.	1.80
90-130	37.47	N.A.	1.80
90-150	37.47	N.A.	1.80
90-180	37.47	N.A.	1.80
110-180	0.11	N.A.	0.00
0-180	2041.36	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	65.74
10-20	188.72
20-30	286.50
30-40	344.38
40-50	352.85
50-60	311.50
60-70	233.98
70-80	146.24
80-90	73.98
90-100	30.13
100-110	7.23
110-120	0.11
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 935.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	44	39	49	43	39	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	37	31	43	36	31	41	35	31	29
9	56	42	34	29	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	26	36	30	25	35	29	25	23


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 935.IES**

**UGR TABLE - CORRECTED**

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	17.8	19.4	18.2	19.8	20.2	19.5	21.1	19.9	21.5	21.9
	3H	19.1	20.6	19.5	20.9	21.3	21.5	23.0	21.9	23.3	23.7
	4H	19.5	20.9	19.9	21.3	21.7	22.3	23.7	22.8	24.1	24.5
	6H	19.7	21.0	20.2	21.4	21.8	23.1	24.4	23.6	24.8	25.2
	8H	19.8	21.0	20.2	21.4	21.9	23.5	24.7	23.9	25.1	25.6
	12H	19.8	21.0	20.3	21.4	21.9	23.8	25.0	24.3	25.4	25.9
4H	2H	18.7	20.1	19.1	20.4	20.9	20.0	21.4	20.4	21.8	22.2
	3H	20.2	21.4	20.6	21.8	22.2	22.2	23.4	22.6	23.8	24.3
	4H	20.7	21.8	21.2	22.2	22.7	23.2	24.3	23.7	24.7	25.2
	6H	21.0	22.0	21.5	22.5	23.0	24.1	25.1	24.6	25.6	26.1
	8H	21.1	22.0	21.6	22.5	23.0	24.6	25.5	25.1	25.9	26.5
	12H	21.2	22.0	21.7	22.5	23.0	25.0	25.8	25.6	26.4	26.9
8H	4H	21.3	22.1	21.7	22.6	23.1	23.4	24.3	23.9	24.8	25.3
	6H	21.8	22.5	22.3	23.0	23.5	24.5	25.3	25.1	25.8	26.3
	8H	21.9	22.6	22.5	23.1	23.7	25.1	25.8	25.7	26.3	26.8
	12H	22.0	22.6	22.6	23.2	23.8	25.7	26.3	26.3	26.8	27.4
12H	4H	21.4	22.2	21.9	22.7	23.2	23.4	24.2	23.9	24.7	25.2
	6H	22.0	22.7	22.5	23.1	23.7	24.6	25.3	25.2	25.8	26.3
	8H	22.2	22.8	22.8	23.3	23.9	25.2	25.8	25.8	26.3	26.9

Maximum UGR = 27.4

POLAR GRAPH



Maximum Candela = 695.074 Located At Horizontal Angle = 90, Vertical Angle = 1.5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (1.5) (Through Max. Cd.)