



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 930.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-013(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/2/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] ECL G2 2 MD UV FR 930

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMP] 28 white LEDs on one LS3872A LED board

[BALLAST] One ULT D700C20UNVPW-C LED driver labeled as 320mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2033
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	127
Total Luminaire Watts	16
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	1.99 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	8433	8215	8291
55	7237	7411	7616
65	5709	6433	6737
75	4054	5440	5732
85	2128	4953	5072

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 930.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	253.39	N.A.	12.50
0-30	538.69	N.A.	26.50
0-40	881.62	N.A.	43.40
0-60	1543.19	N.A.	75.90
0-80	1921.82	N.A.	94.50
0-90	1995.48	N.A.	98.20
10-90	1930.02	N.A.	94.90
20-40	628.23	N.A.	30.90
20-50	979.61	N.A.	48.20
40-70	894.57	N.A.	44.00
60-80	378.62	N.A.	18.60
70-80	145.62	N.A.	7.20
80-90	73.66	N.A.	3.60
90-110	37.20	N.A.	1.80
90-120	37.31	N.A.	1.80
90-130	37.31	N.A.	1.80
90-150	37.31	N.A.	1.80
90-180	37.31	N.A.	1.80
110-180	0.11	N.A.	0.00
0-180	2032.79	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	65.46
10-20	187.93
20-30	285.30
30-40	342.93
40-50	351.37
50-60	310.20
60-70	233.00
70-80	145.62
80-90	73.66
90-100	30.00
100-110	7.20
110-120	0.11
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 930.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	44	39	49	43	39	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	37	31	42	36	31	41	35	31	29
9	56	42	34	29	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	26	36	30	25	35	29	25	23

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL G2 2 MD UV FR 930.IES

UGR TABLE - CORRECTED


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	17.8	19.4	18.2	19.8	20.2	19.5	21.1	19.9	21.5	21.9
	3H	19.1	20.6	19.5	20.9	21.3	21.5	23.0	21.9	23.3	23.7
	4H	19.5	20.9	19.9	21.3	21.7	22.3	23.7	22.8	24.1	24.5
	6H	19.7	21.0	20.2	21.4	21.8	23.1	24.4	23.5	24.8	25.2
	8H	19.8	21.0	20.2	21.4	21.9	23.5	24.7	23.9	25.1	25.6
	12H	19.8	21.0	20.3	21.4	21.9	23.8	25.0	24.3	25.4	25.9
4H	2H	18.7	20.0	19.1	20.4	20.9	20.0	21.4	20.4	21.8	22.2
	3H	20.2	21.4	20.6	21.8	22.2	22.2	23.4	22.6	23.8	24.3
	4H	20.7	21.8	21.2	22.2	22.7	23.2	24.3	23.7	24.7	25.2
	6H	21.0	22.0	21.5	22.5	23.0	24.1	25.1	24.6	25.6	26.1
	8H	21.1	22.0	21.6	22.5	23.0	24.6	25.5	25.1	25.9	26.4
	12H	21.2	22.0	21.7	22.5	23.0	25.0	25.8	25.6	26.3	26.9
8H	4H	21.3	22.1	21.7	22.6	23.1	23.4	24.3	23.9	24.8	25.3
	6H	21.8	22.5	22.3	23.0	23.5	24.5	25.3	25.1	25.8	26.3
	8H	21.9	22.6	22.5	23.1	23.7	25.1	25.8	25.7	26.3	26.8
	12H	22.0	22.6	22.6	23.2	23.8	25.7	26.3	26.3	26.8	27.4
12H	4H	21.4	22.2	21.9	22.7	23.2	23.4	24.2	23.9	24.7	25.2
	6H	22.0	22.6	22.5	23.1	23.7	24.6	25.3	25.1	25.7	26.3
	8H	22.2	22.8	22.8	23.3	23.9	25.2	25.8	25.7	26.3	26.9

Maximum UGR = 27.4

POLAR GRAPH



Maximum Candela = 692.157 Located At Horizontal Angle = 90, Vertical Angle = 1.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (1.5) (Through Max. Cd.)