



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 6 HI UV FR 935.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-018(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/1/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] ECL G2 6 HI UV FR 935

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMP] 144 white LEDs on three LS3872A LED boards

[BALLAST] One ULT D15CC55UNVPW-C LED driver labeled as 1220mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	9145
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	147
Total Luminaire Watts	62.2
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	6.00 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	12909	12404	12352
55	11276	11270	11345
65	9096	9872	10015
75	6653	8463	8479
85	3946	7938	7437

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL G2 6 HI UV FR 935.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	1136.94	N.A.	12.40
0-30	2417.82	N.A.	26.40
0-40	3958.93	N.A.	43.30
0-60	6939.75	N.A.	75.90
0-80	8650.8	N.A.	94.60
0-90	8981.47	N.A.	98.20
10-90	8687.89	N.A.	95.00
20-40	2821.99	N.A.	30.90
20-50	4403.29	N.A.	48.20
40-70	4034.44	N.A.	44.10
60-80	1711.05	N.A.	18.70
70-80	657.42	N.A.	7.20
80-90	330.67	N.A.	3.60
90-110	163.00	N.A.	1.80
90-120	163.34	N.A.	1.80
90-130	163.34	N.A.	1.80
90-150	163.34	N.A.	1.80
90-180	163.34	N.A.	1.80
110-180	0.33	N.A.	0.00
0-180	9144.81	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	293.58
10-20	843.36
20-30	1280.88
30-40	1541.11
40-50	1581.3
50-60	1399.52
60-70	1053.63
70-80	657.42
80-90	330.67
90-100	132.55
100-110	30.45
110-120	0.33
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL G2 6 HI UV FR 935.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	49	43	38	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	36	31	42	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23


IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL G2 6 HI UV FR 935.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	19.3	20.9	19.7	21.3	21.6	21.0	22.6	21.4	23.0	23.3
	3H	20.6	22.1	21.0	22.4	22.8	23.0	24.4	23.4	24.8	25.2
	4H	21.0	22.4	21.4	22.8	23.2	23.8	25.2	24.3	25.6	26.0
	6H	21.2	22.5	21.7	22.9	23.3	24.6	25.9	25.1	26.3	26.8
	8H	21.3	22.5	21.7	22.9	23.4	25.0	26.2	25.5	26.7	27.1
	12H	21.3	22.5	21.8	22.9	23.4	25.4	26.6	25.9	27.0	27.5
4H	2H	20.1	21.5	20.6	21.9	22.3	21.5	22.8	21.9	23.2	23.7
	3H	21.7	22.8	22.1	23.3	23.7	23.7	24.8	24.1	25.3	25.7
	4H	22.2	23.3	22.7	23.7	24.2	24.7	25.7	25.2	26.2	26.7
	6H	22.6	23.5	23.0	24.0	24.5	25.7	26.6	26.1	27.1	27.6
	8H	22.6	23.5	23.1	24.0	24.5	26.1	27.0	26.6	27.5	28.0
	12H	22.7	23.5	23.2	24.0	24.5	26.6	27.4	27.1	27.9	28.4
8H	4H	22.8	23.6	23.3	24.1	24.6	24.9	25.8	25.4	26.3	26.8
	6H	23.3	24.0	23.8	24.5	25.1	26.1	26.8	26.6	27.3	27.8
	8H	23.5	24.1	24.0	24.7	25.2	26.7	27.3	27.2	27.8	28.4
	12H	23.6	24.2	24.1	24.7	25.3	27.3	27.9	27.8	28.4	29.0
12H	4H	22.9	23.7	23.4	24.2	24.7	24.9	25.7	25.4	26.2	26.7
	6H	23.5	24.2	24.1	24.7	25.2	26.1	26.8	26.7	27.3	27.9
	8H	23.7	24.3	24.3	24.9	25.5	26.8	27.3	27.3	27.9	28.5

Maximum UGR = 29.0

POLAR GRAPH



Maximum Candela = 3107.577 Located At Horizontal Angle = 90, Vertical Angle = 3.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (3.5) (Through Max. Cd.)