



IES INDOOR REPORT

PHOTOMETRIC FILENAME : NVL G2 2 HI UV FRA 935.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001796-005(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 7/6/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] NVL G2 2 HI UV FRA 935

[LUMINAIRE] Surface/pendant mounted, formed white plastic housing, formed

[MORE] white painted steel LED tray/reflector, translucent linear stepped plastic

[MORE] lens.

[LAMP] 64 white LEDs on one LS3872A8-3500K-R90 LED board

[BALLAST] One ULT Everline D10CC30UNVPW-C LED driver at 590mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4129
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	135
Total Luminaire Watts	30.5
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	2.27 ft
Luminous Width (90-270)	0.54 ft
Luminous Height	0.16 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	9502	8588	8356
55	8302	7423	8379
65	6867	6786	7880
75	5360	5614	6364
85	3648	4160	4585

IES INDOOR REPORT
PHOTOMETRIC FILENAME : NVL G2 2 HI UV FRA 935.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	490.75	N.A.	11.90
0-30	1044.63	N.A.	25.30
0-40	1705.26	N.A.	41.30
0-60	2976.77	N.A.	72.10
0-80	3800.85	N.A.	92.10
0-90	3964.29	N.A.	96.00
10-90	3837.9	N.A.	93.00
20-40	1214.52	N.A.	29.40
20-50	1878.46	N.A.	45.50
40-70	1767.88	N.A.	42.80
60-80	824.08	N.A.	20.00
70-80	327.70	N.A.	7.90
80-90	163.44	N.A.	4.00
90-110	122.76	N.A.	3.00
90-120	149.24	N.A.	3.60
90-130	160.73	N.A.	3.90
90-150	164.30	N.A.	4.00
90-180	164.45	N.A.	4.00
110-180	41.69	N.A.	1.00
0-180	4128.74	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	126.38
10-20	364.36
20-30	553.89
30-40	660.63
40-50	663.94
50-60	607.57
60-70	496.38
70-80	327.70
80-90	163.44
90-100	76.68
100-110	46.08
110-120	26.48
120-130	11.49
130-140	2.77
140-150	0.80
150-160	0.15
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : NVL G2 2 HI UV FRA 935.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	103	103	103	98	98	98	96
1	107	102	97	93	104	99	95	91	94	90	87	89	86	84	85	83	81	78
2	97	88	81	75	94	86	79	74	82	76	71	78	73	69	74	70	67	64
3	88	77	69	62	85	75	67	61	72	65	59	68	63	58	65	60	56	54
4	81	68	59	52	78	67	58	52	64	56	50	61	54	49	58	53	48	46
5	74	61	52	45	72	59	51	44	57	49	44	54	48	43	52	46	42	40
6	68	55	46	39	66	54	45	39	51	44	38	49	43	37	47	41	37	35
7	63	50	41	35	61	49	40	34	47	39	34	45	38	33	43	37	33	31
8	59	45	37	31	57	44	36	31	43	35	30	41	35	30	40	34	29	27
9	55	42	33	28	53	41	33	27	39	32	27	38	31	27	37	31	26	25
10	52	38	30	25	50	38	30	25	36	29	25	35	29	24	34	28	24	22

IES INDOOR REPORT
PHOTOMETRIC FILENAME : NVL G2 2 HI UV FRA 935.IES

UGR TABLE - CORRECTED


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	17.7	19.3	18.1	19.7	20.1	19.9	21.5	20.4	21.9	22.3
	3H	19.1	20.5	19.5	20.9	21.4	22.2	23.6	22.6	24.0	24.5
	4H	19.6	20.9	20.0	21.3	21.8	23.1	24.4	23.6	24.9	25.3
	6H	19.9	21.1	20.4	21.6	22.1	23.9	25.1	24.4	25.6	26.1
	8H	20.0	21.2	20.5	21.6	22.1	24.2	25.4	24.7	25.9	26.4
	12H	20.0	21.2	20.5	21.6	22.2	24.5	25.7	25.0	26.1	26.7
4H	2H	18.6	19.9	19.0	20.4	20.8	20.3	21.7	20.8	22.1	22.6
	3H	20.2	21.4	20.7	21.8	22.3	22.8	24.0	23.3	24.4	24.9
	4H	20.8	21.8	21.3	22.3	22.8	23.9	24.9	24.4	25.4	25.9
	6H	21.2	22.1	21.7	22.6	23.2	24.9	25.8	25.4	26.3	26.8
	8H	21.3	22.2	21.9	22.7	23.3	25.3	26.1	25.8	26.6	27.2
	12H	21.4	22.2	22.0	22.8	23.3	25.7	26.4	26.2	27.0	27.5
8H	4H	21.4	22.2	21.9	22.8	23.3	24.1	24.9	24.6	25.4	26.0
	6H	21.9	22.7	22.5	23.2	23.8	25.2	25.9	25.7	26.5	27.0
	8H	22.2	22.8	22.7	23.4	24.0	25.7	26.4	26.3	26.9	27.5
	12H	22.3	22.9	22.9	23.4	24.1	26.2	26.8	26.8	27.4	28.0
12H	4H	21.5	22.3	22.0	22.8	23.4	24.1	24.9	24.6	25.4	26.0
	6H	22.2	22.8	22.7	23.3	24.0	25.2	25.9	25.8	26.4	27.0
	8H	22.4	23.0	23.0	23.6	24.2	25.8	26.4	26.4	26.9	27.6

Maximum UGR = 28.0

POLAR GRAPH



Maximum Candela = 1342.221 Located At Horizontal Angle = 90, Vertical Angle = 5.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (5.5) (Through Max. Cd.)