



IES INDOOR REPORT

PHOTOMETRIC FILENAME : NVL G2 4 VL UV FRA 935.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001796-008A(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 7/6/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] NVL G2 4 VL UV FRA 935

[LUMINAIRE] Surface/pendant mounted, formed white plastic housing, formed
[MORE] white painted steel LED tray/reflector, translucent linear stepped plastic
[MORE] lens.

[LAMP] 56 white LEDs on two LS3872A6-3500K-R90 LED boards with 28 LEDs
[MORE] each.

[BALLAST] One ULT Everline D700C20UNVPW-C LED driver labeled as 340mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2037
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	127
Total Luminaire Watts	16.1
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.22
Spacing Criterion (90-270)	1.20
Spacing Criterion (Diagonal)	1.32
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	4.27 ft
Luminous Width (90-270)	0.54 ft
Luminous Height	0.16 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	2623	2274	2224
55	2250	1945	2001
65	1821	1655	1857
75	1390	1445	1723
85	882	1308	1557

IES INDOOR REPORT
PHOTOMETRIC FILENAME : NVL G2 4 VL UV FRA 935.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	249.80	N.A.	12.30
0-30	521.21	N.A.	25.60
0-40	843.37	N.A.	41.40
0-60	1456.31	N.A.	71.50
0-80	1838.36	N.A.	90.20
0-90	1929.87	N.A.	94.70
10-90	1864.33	N.A.	91.50
20-40	593.57	N.A.	29.10
20-50	919.54	N.A.	45.10
40-70	838.74	N.A.	41.20
60-80	382.04	N.A.	18.80
70-80	156.25	N.A.	7.70
80-90	91.52	N.A.	4.50
90-110	83.36	N.A.	4.10
90-120	99.36	N.A.	4.90
90-130	105.58	N.A.	5.20
90-150	107.11	N.A.	5.30
90-180	107.22	N.A.	5.30
110-180	23.85	N.A.	1.20
0-180	2037.09	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	65.54
10-20	184.25
20-30	271.41
30-40	322.16
40-50	325.97
50-60	286.98
60-70	225.80
70-80	156.25
80-90	91.52
90-100	52.35
100-110	31.01
110-120	15.99
120-130	6.22
130-140	1.20
140-150	0.32
150-160	0.11
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : NVL G2 4 VL UV FRA 935.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	114	114	114	114	108	108	108	102	102	102	97	97	97	95
1	106	101	96	92	103	98	94	90	93	90	86	88	85	83	84	82	79	77
2	97	88	81	75	93	86	79	73	81	76	71	77	72	68	73	69	66	64
3	88	77	69	62	85	75	67	61	71	65	59	68	62	58	65	60	56	53
4	81	68	59	52	78	67	58	52	63	56	51	60	54	49	58	52	48	46
5	74	61	52	45	72	60	51	45	57	49	44	54	48	43	52	46	42	40
6	68	55	46	39	66	54	45	39	51	44	38	49	43	38	47	41	37	35
7	63	50	41	35	61	49	40	35	47	39	34	45	38	33	43	37	33	31
8	59	46	37	31	57	45	37	31	43	36	30	41	35	30	40	34	29	27
9	55	42	34	28	54	41	33	28	39	32	27	38	32	27	37	31	27	25
10	52	39	31	25	50	38	30	25	37	30	25	35	29	25	34	28	24	22

IES INDOOR REPORT
PHOTOMETRIC FILENAME : NVL G2 4 VL UV FRA 935.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20


Room Size UGR Viewed Crosswise

UGR Viewed Endwise

X=2H	Y=2H	13.0	14.5	13.4	15.0	15.4	14.7	16.3	15.2	16.7	17.1
	3H	14.3	15.7	14.7	16.1	16.6	17.1	18.5	17.6	18.9	19.4
	4H	14.7	16.0	15.2	16.5	17.0	18.2	19.6	18.7	20.0	20.5
	6H	15.0	16.2	15.5	16.7	17.2	19.3	20.6	19.8	21.0	21.5
	8H	15.0	16.2	15.5	16.7	17.2	19.8	21.0	20.3	21.5	22.0
	12H	15.0	16.2	15.6	16.7	17.2	20.4	21.5	20.9	22.0	22.6
4H	2H	13.7	15.1	14.2	15.5	16.0	15.1	16.5	15.6	16.9	17.4
	3H	15.3	16.4	15.8	16.9	17.4	17.7	18.9	18.2	19.4	19.9
	4H	15.8	16.9	16.3	17.4	17.9	19.0	20.1	19.5	20.6	21.1
	6H	16.2	17.1	16.7	17.6	18.2	20.3	21.2	20.9	21.8	22.3
	8H	16.3	17.2	16.8	17.7	18.3	21.0	21.8	21.5	22.3	22.9
	12H	16.4	17.1	16.9	17.7	18.3	21.6	22.4	22.2	23.0	23.5
8H	4H	16.4	17.3	17.0	17.8	18.4	19.2	20.1	19.8	20.6	21.2
	6H	17.0	17.7	17.5	18.3	18.9	20.7	21.4	21.2	22.0	22.6
	8H	17.2	17.8	17.7	18.4	19.0	21.4	22.1	22.0	22.7	23.3
	12H	17.3	17.9	17.9	18.5	19.1	22.3	22.9	22.9	23.4	24.1
12H	4H	16.6	17.4	17.2	17.9	18.5	19.2	20.0	19.8	20.6	21.1
	6H	17.3	17.9	17.8	18.5	19.1	20.7	21.4	21.3	21.9	22.6
	8H	17.5	18.1	18.1	18.7	19.3	21.5	22.1	22.1	22.7	23.4

Maximum UGR = 24.1

POLAR GRAPH



Maximum Candela = 697.848 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)