



IES INDOOR REPORT

PHOTOMETRIC FILENAME : PBL V2 4W HI UV 850.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001687-021

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 4/20/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] PBL V2 4W HI UV 850

[LUMINAIRE] High Bay mounted, formed white painted aluminum housing/reflector,

[MORE] no enclosure.

[LAMP] 504 white LEDs, six ULT M900C85084N2Q LED boards

[BALLAST] Three ULT D21CC80UNVPW-D LED drivers labeled at 1900mA

[OTHER] 120.1Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	40198
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	158
Total Luminaire Watts	254.1
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.40
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	3.80 ft
Luminous Width (90-270)	1.26 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	30887	30313	30477
55	30303	29646	30041
65	28644	28141	28926
75	23890	25841	10027
85	12269	7810	8461

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV 850.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	5022.13	N.A.	12.50
0-30	10730.53	N.A.	26.70
0-40	17723.58	N.A.	44.10
0-60	31913.25	N.A.	79.40
0-80	39741.85	N.A.	98.90
0-90	40193.82	N.A.	100.00
10-90	38897.76	N.A.	96.80
20-40	12701.45	N.A.	31.60
20-50	20089.43	N.A.	50.00
40-70	19459.66	N.A.	48.40
60-80	7828.6	N.A.	19.50
70-80	2558.6	N.A.	6.40
80-90	451.97	N.A.	1.10
90-110	4.49	N.A.	0.00
90-120	4.49	N.A.	0.00
90-130	4.49	N.A.	0.00
90-150	4.49	N.A.	0.00
90-180	4.49	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	40198.3	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	1296.06
10-20	3726.07
20-30	5708.39
30-40	6993.05
40-50	7387.98
50-60	6801.69
60-70	5269.99
70-80	2558.6
80-90	451.97
90-100	4.38
100-110	0.10
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV 850.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	95	98	95	92	94	91	89	90	88	86	84
2	99	91	84	78	96	89	83	77	85	80	76	82	78	74	79	75	72	70
3	90	80	71	65	88	78	70	64	75	68	63	72	67	62	70	65	61	59
4	82	70	62	55	80	69	61	54	66	59	54	64	58	53	62	57	52	50
5	76	63	54	47	74	62	53	47	59	52	46	57	51	46	56	50	45	43
6	70	56	47	41	68	55	47	41	54	46	40	52	45	40	50	44	40	38
7	65	51	42	36	63	50	42	36	49	41	36	47	40	35	46	40	35	33
8	60	46	38	32	59	46	38	32	44	37	32	43	36	32	42	36	31	29
9	56	43	34	29	55	42	34	29	41	34	29	40	33	28	39	33	28	26
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	26	24


IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV 850.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	24.0	25.7	24.4	26.0	26.3	24.2	25.8	24.5	26.1	26.5
	3H	25.9	27.4	26.3	27.7	28.1	26.1	27.6	26.5	28.0	28.3
	4H	26.5	27.9	26.9	28.3	28.7	26.2	27.7	26.6	28.0	28.4
	6H	27.0	28.3	27.4	28.6	29.0	26.3	27.6	26.7	28.0	28.4
	8H	27.1	28.3	27.5	28.7	29.1	26.3	27.6	26.7	27.9	28.3
	12H	27.1	28.3	27.5	28.7	29.1	26.3	27.5	26.8	27.9	28.3
4H	2H	24.7	26.1	25.1	26.4	26.8	24.8	26.2	25.2	26.6	26.9
	3H	26.8	27.9	27.2	28.3	28.7	27.0	28.2	27.4	28.6	29.0
	4H	27.5	28.6	28.0	29.0	29.4	27.1	28.2	27.6	28.6	29.0
	6H	28.1	29.0	28.5	29.4	29.9	27.2	28.2	27.7	28.6	29.1
	8H	28.2	29.1	28.7	29.5	30.0	27.3	28.1	27.7	28.6	29.0
	12H	28.3	29.1	28.8	29.5	30.0	27.3	28.1	27.8	28.5	29.0
8H	4H	27.8	28.7	28.3	29.1	29.6	27.4	28.3	27.9	28.7	29.2
	6H	28.4	29.1	28.9	29.6	30.1	27.6	28.3	28.0	28.7	29.2
	8H	28.6	29.3	29.1	29.8	30.2	27.6	28.2	28.1	28.7	29.2
	12H	28.7	29.3	29.2	29.7	30.3	27.6	28.2	28.1	28.7	29.2
12H	4H	27.8	28.6	28.3	29.0	29.5	27.4	28.2	27.9	28.7	29.2
	6H	28.4	29.0	28.9	29.5	30.0	27.6	28.2	28.1	28.7	29.2
	8H	28.6	29.2	29.1	29.7	30.2	27.6	28.2	28.1	28.7	29.2

Maximum UGR = 30.3

POLAR GRAPH



Maximum Candela = 13786.289 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)