IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV FR 850.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] LLIA001687-022
[TESTLAB] LightLab International Allentown, LLC
[ISSUEDATE] 4/20/2022
[MANUFAC] Lumen Focus, LLC
[LUMCAT] PBL V2 4W HI UV FR 850
[LUMINAIRE] High Bay mounted, formed white painted aluminum housing/reflector,
[MORE] three curved translucent plastic enclosures.
[LAMP] 504 white LEDs, six ULT M900C85084N2Q LED boards
[BALLAST] Three ULT D21CC80UNVPW-C LED drivers labeled at 1900mA
[OTHER] 120.0Vac, 60.00Hz
[OTHER] This test was performed using the absolute method of photometry.
[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	37866
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	149
Total Luminaire Watts	254.1
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	3.80 ft
Luminous Width (90-270)	1.26 ft
Luminous Height	0.04 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	25880	27251	28416
55	22613	25841	27721
65	18453	24247	26915
75	13827	22474	19301
85	8643	13139	12509

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV FR 850.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	4883.39	N.A.	12.90
0-30	10371.21	N.A.	27.40
0-40	16969.68	N.A.	44.80
0-60	29808.6	N.A.	78.70
0-80	37064.5	N.A.	97.90
0-90	37830.35	N.A.	99.90
10-90	36566.81	N.A.	96.60
20-40	12086.29	N.A.	31.90
20-50	18871.99	N.A.	49.80
40-70	17470.26	N.A.	46.10
60-80	7255.91	N.A.	19.20
70-80	2624.57	N.A.	6.90
80-90	765.84	N.A.	2.00
90-110	35.95	N.A.	0.10
90-120	35.95	N.A.	0.10
90-130	35.95	N.A.	0.10
90-150	35.95	N.A.	0.10
90-180	35.95	N.A.	0.10
110-180	0.00	N.A.	0.00
0-180	37866.3	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	1263.54
10-20	3619.85
20-30	5487.82
30-40	6598.47
40-50	6785.7
50-60	6053.22
60-70	4631.34
70-80	2624.57
80-90	765.84
90-100	35.85
100-110	0.11
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV FR 850.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	96	106	102	98	94	97	94	91	93	91	88	90	88	86	83
2	99	90	84	78	96	89	82	77	85	80	75	82	77	73	79	75	72	69
3	90	79	71	65	87	78	70	64	75	68	63	72	66	62	69	65	61	58
4	82	70	61	55	80	69	61	54	66	59	54	64	58	53	62	57	52	50
5	76	63	54	47	74	62	53	47	60	52	46	58	51	46	56	50	45	43
6	70	57	48	41	68	56	47	41	54	46	41	52	45	40	50	44	40	38
7	65	51	42	36	63	50	42	36	49	41	36	47	41	36	46	40	35	33
8	60	47	38	32	59	46	38	32	45	37	32	43	37	32	42	36	32	30
9	56	43	35	29	55	42	34	29	41	34	29	40	33	29	39	33	29	27
10	53	40	32	26	52	39	31	26	38	31	26	37	31	26	36	30	26	24

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV FR 850.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
Floor Cavity		20	20	20	20	20	20	20	20	20	20
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	22.4	24.1	22.8	24.4	24.7	24.0	25.6	24.4	26.0	26.3
	3H	23.9	25.4	24.3	25.7	26.1	26.0	27.5	26.4	27.9	28.2
	4H	24.4	25.8	24.8	26.1	26.5	26.6	28.0	27.0	28.4	28.8
	6H	24.7	26.0	25.1	26.4	26.8	26.9	28.2	27.4	28.6	29.0
	8H	24.8	26.0	25.2	26.4	26.8	27.0	28.3	27.4	28.6	29.0
	12H	24.9	26.0	25.3	26.4	26.9	27.1	28.3	27.5	28.7	29.1
4H	2H	23.4	24.8	23.8	25.1	25.5	24.5	25.9	24.9	26.3	26.7
	3H	25.1	26.3	25.5	26.7	27.0	26.8	28.0	27.3	28.4	28.8
	4H	25.7	26.8	26.1	27.2	27.6	27.6	28.6	28.0	29.0	29.5
	6H	26.1	27.1	26.6	27.5	28.0	28.0	28.9	28.4	29.3	29.8
	8H	26.3	27.1	26.7	27.6	28.1	28.1	28.9	28.5	29.4	29.8
	12H	26.4	27.1	26.8	27.6	28.1	28.2	29.0	28.7	29.4	29.9
8H	4H	26.2	27.1	26.7	27.5	28.0	27.8	28.7	28.3	29.1	29.6
	6H	26.8	27.6	27.3	28.1	28.5	28.3	29.1	28.8	29.5	30.0
	8H	27.0	27.7	27.5	28.2	28.7	28.5	29.1	29.0	29.7	30.1
	12H	27.2	27.8	27.7	28.3	28.8	28.7	29.2	29.2	29.7	30.3
12H	4H	26.3	27.1	26.8	27.5	28.0	27.8	28.6	28.3	29.1	29.6
	6H	26.9	27.6	27.4	28.0	28.6	28.4	29.0	28.9	29.5	30.0
	8H	27.2	27.8	27.7	28.3	28.8	28.6	29.2	29.1	29.7	30.2

Maximum UGR = 30.3

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL V2 4W HI UV FR 850.IES

POLAR GRAPH



Maximum Candela = 13368.769 Located At Horizontal Angle = 90, Vertical Angle = 1.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (1.5) (Through Max. Cd.)

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.