



IES INDOOR REPORT

PHOTOMETRIC FILENAME : PBL A G2 8 VH UV 850.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001853-007A(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 9/6/2022

[MANUFAC] Lumen Focus, LLC

[LUMCAT] PBL A G2 8 VH UV 850

[LUMINAIRE] Surface/pendant mounted, formed white painted steel housing,

[MORE] formed and fabricated specular aluminum reflector, no enclosure.

[LAMP] 896 white LEDs, eight M12CC850D112N2U LED boards with 112 LEDs each

[BALLAST] Four ULT D21CC80UNVPW-C LED drivers set at 1740mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	56541
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	164
Total Luminaire Watts	344.5
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.30
Spacing Criterion (90-270)	1.04
Spacing Criterion (Diagonal)	1.22
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	7.83 ft
Luminous Width (90-270)	0.52 ft
Luminous Height	0.03 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	86848	44195	12711
55	84155	11596	110
65	78011	319	44
75	64831	209	17
85	33842	40	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL A G2 8 VH UV 850.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	11258.67	N.A.	19.90
0-30	23631.59	N.A.	41.80
0-40	36894.3	N.A.	65.30
0-60	52603.42	N.A.	93.00
0-80	56341.21	N.A.	99.60
0-90	56540.75	N.A.	100.00
10-90	53641.41	N.A.	94.90
20-40	25635.63	N.A.	45.30
20-50	35521.06	N.A.	62.80
40-70	18513.19	N.A.	32.70
60-80	3737.79	N.A.	6.60
70-80	933.72	N.A.	1.70
80-90	199.54	N.A.	0.40
90-110	0.38	N.A.	0.00
90-120	0.38	N.A.	0.00
90-130	0.38	N.A.	0.00
90-150	0.38	N.A.	0.00
90-180	0.38	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	56541.12	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	2899.34
10-20	8359.33
20-30	12372.91
30-40	13262.71
40-50	9885.43
50-60	5823.68
60-70	2804.07
70-80	933.72
80-90	199.54
90-100	0.38
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL A G2 8 VH UV 850.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	105	102	109	106	103	100	101	99	97	98	96	94	94	93	91	89
2	104	97	92	87	101	95	90	86	92	88	84	89	85	82	86	83	81	79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	71	70
4	89	79	72	67	87	78	71	66	76	70	65	74	69	65	72	67	64	62
5	83	72	65	59	81	71	64	59	69	63	58	67	62	58	66	61	57	55
6	78	66	58	53	76	65	58	53	64	57	52	62	56	52	60	55	51	50
7	72	61	53	48	71	60	53	48	58	52	47	57	51	47	56	51	47	45
8	68	56	48	43	66	55	48	43	54	48	43	53	47	43	52	46	42	41
9	64	52	44	39	62	51	44	39	50	44	39	49	43	39	48	43	39	37
10	60	48	41	36	59	48	41	36	47	40	36	46	40	36	45	40	36	34


IES INDOOR REPORT
PHOTOMETRIC FILENAME : PBL A G2 8 VH UV 850.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	28.0	29.4	28.4	29.7	30.0	14.0	14.0	14.0	14.0	14.0
	3H	29.1	30.3	29.5	30.6	31.0	14.0	14.0	14.0	14.0	14.0
	4H	29.5	30.7	30.0	31.0	31.4	14.0	14.0	14.0	14.0	14.0
	6H	29.9	30.9	30.3	31.3	31.7	14.0	14.0	14.0	14.0	14.0
	8H	30.0	31.0	30.4	31.4	31.8	14.0	14.0	14.0	14.0	14.0
	12H	30.1	31.0	30.5	31.4	31.8	14.0	14.0	14.0	14.0	14.0
4H	2H	27.8	28.9	28.2	29.3	29.7	14.0	14.0	14.0	14.0	14.0
	3H	28.9	29.8	29.3	30.2	30.6	14.0	14.0	14.0	14.0	14.0
	4H	29.3	30.1	29.7	30.5	31.0	14.0	14.0	14.0	14.0	14.0
	6H	29.7	30.4	30.2	30.9	31.3	14.0	14.0	14.0	14.0	14.0
	8H	29.9	30.5	30.3	31.0	31.4	14.0	14.0	14.0	14.0	14.0
	12H	29.9	30.5	30.4	31.0	31.5	14.0	14.0	14.0	14.0	14.0
8H	4H	29.2	29.8	29.7	30.3	30.7	14.0	14.0	14.0	14.0	14.0
	6H	29.6	30.1	30.1	30.6	31.1	14.0	14.0	14.0	14.0	14.0
	8H	29.7	30.2	30.2	30.7	31.2	14.0	14.0	14.0	14.0	14.0
	12H	29.8	30.2	30.3	30.7	31.3	14.0	14.0	14.0	14.0	14.0
12H	4H	29.1	29.7	29.6	30.2	30.7	14.0	14.0	14.0	14.0	14.0
	6H	29.5	30.0	30.1	30.5	31.0	14.0	14.0	14.0	14.0	14.0
	8H	29.6	30.1	30.2	30.6	31.1	14.0	14.0	14.0	14.0	14.0

Maximum UGR = 31.8

POLAR GRAPH



Maximum Candela = 33502.81 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)