IES INDOOR REPORT
PHOTOMETRIC FILENAME : DLS V2 6 SEL UV SW 9SEL [MD,927].IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] JG202002002V
[TESTLAB] EVERFINE
[TESTDATE] 2021-09-28
[ISSUEDATE] 2021-10-08 14:56:07
[NEARFIELD]
[LAMPPOSITION] 0,0
[OTHER] EVERFINE GO-2000B_V1 SYSTEM
[MANUFAC] LumenFocus, LLC.
[LUMINAIRE] LED 6" Can - 15W/27K/Dim/100-277V
[LUMCAT] DLS v2 6 SEL UV SW 9SEL [MD,927]

CHARACTERISTICS

Lumens Per Lamp	1219.6 (1 lamp)
Total Lamp Lumens	1219.6
Luminaire Lumens	1220
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	85
Total Luminaire Watts	14.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.20
Spacing Criterion (Diagonal)	1.28
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.15 m (Diameter)
Luminous Width (90-270)	0.15 m (Diameter)
Luminous Height	0.00 m

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	24372	24813	24789
55	16010	17035	17464
65	8961	9988	10901
75	3921	4822	5953
85	1443	2165	3254

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : DLS V2 6 SEL UV SW 9SEL [MD,927].IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	211.14	17.30	17.30
0-30	441.10	36.20	36.20
0-40	702.22	57.60	57.60
0-60	1099.08	90.10	90.10
0-80	1204.14	98.70	98.70
0-90	1208.59	99.10	99.10
10-90	1153.64	94.60	94.60
20-40	491.07	40.30	40.30
20-50	729.14	59.80	59.80
40-70	475.66	39.00	39.00
60-80	105.06	8.60	8.60
70-80	26.25	2.20	2.20
80-90	4.45	0.40	0.40
90-110	1.17	0.10	0.10
90-120	2.46	0.20	0.20
90-130	4.14	0.30	0.30
90-150	7.90	0.60	0.60
90-180	11.01	0.90	0.90
110-180	9.84	0.80	0.80
0-180	1219.6	100.00	100.00

Total Luminaire Efficiency = 100.00%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	54.95
10-20	156.20
20-30	229.95
30-40	261.12
40-50	238.06
50-60	158.80
60-70	78.80
70-80	26.25
80-90	4.45
90-100	0.38
100-110	0.79
110-120	1.28
120-130	1.68
130-140	1.89
140-150	1.86
150-160	1.60
160-170	1.11
170-180	0.40

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : DLS V2 6 SEL UV SW 9SEL [MD,927].IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	111	107	103	100	108	105	101	99	100	98	95	96	94	92	93	91	89	87
2	102	95	90	85	100	94	88	84	90	86	82	87	83	80	84	81	78	76
3	95	85	79	73	92	84	77	72	81	75	71	78	74	70	76	72	68	66
4	87	77	69	63	85	76	68	63	73	67	62	71	65	61	69	64	60	58
5	81	70	62	56	79	68	61	55	66	60	55	64	59	54	62	57	53	51
6	75	63	55	49	73	62	55	49	60	54	49	59	53	48	57	52	48	46
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	48	43	39	37
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	39	35	34
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	36	32	31

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : DLS V2 6 SEL UV SW 9SEL [MD,927].IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
Floor Cavity		20	20	20	20	20	20	20	20	20	20
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	19.5	21.0	19.9	21.3	21.6	19.9	21.3	20.2	21.6	22.0
	3H	20.1	21.4	20.5	21.7	22.1	20.6	21.9	21.0	22.3	22.6
	4H	20.2	21.4	20.6	21.7	22.1	20.8	22.0	21.2	22.4	22.8
	6H	20.2	21.3	20.6	21.7	22.1	20.9	22.0	21.3	22.4	22.8
	8H	20.2	21.2	20.6	21.6	22.0	20.9	21.9	21.3	22.3	22.8
	12H	20.1	21.1	20.6	21.5	22.0	20.9	21.9	21.3	22.3	22.7
4H	2H	19.9	21.1	20.3	21.4	21.8	20.1	21.3	20.5	21.7	22.1
	3H	20.6	21.5	21.0	22.0	22.4	21.0	22.0	21.5	22.4	22.8
	4H	20.7	21.5	21.1	22.0	22.4	21.3	22.1	21.7	22.6	23.0
	6H	20.7	21.5	21.2	21.9	22.4	21.4	22.1	21.8	22.6	23.1
	8H	20.7	21.4	21.2	21.9	22.4	21.4	22.1	21.9	22.5	23.0
	12H	20.7	21.3	21.2	21.8	22.3	21.4	22.0	21.9	22.5	23.0
8H	4H	20.7	21.4	21.2	21.9	22.4	21.3	22.0	21.7	22.4	22.9
	6H	20.8	21.3	21.3	21.8	22.3	21.4	22.0	21.9	22.5	23.0
	8H	20.7	21.3	21.3	21.8	22.3	21.4	21.9	21.9	22.5	23.0
	12H	20.7	21.2	21.3	21.7	22.3	21.4	21.9	22.0	22.4	23.0
12H	4H	20.7	21.3	21.2	21.8	22.3	21.2	21.8	21.7	22.3	22.8
	6H	20.7	21.2	21.3	21.7	22.3	21.3	21.9	21.9	22.4	22.9
	8H	20.7	21.2	21.3	21.7	22.3	21.4	21.9	21.9	22.4	23.0

Maximum UGR = 23.1

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES INDOOR REPORT
PHOTOMETRIC FILENAME : DLS V2 6 SEL UV SW 9SEL [MD,927].IES

POLAR GRAPH



Maximum Candela = 581.75 Located At Horizontal Angle = 15, Vertical Angle = 1
1 - Vertical Plane Through Horizontal Angles (15 - 195) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (1) (Through Max. Cd.)

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.