

# NVL G2

## LED Vaportight

The NVL G2 features durable materials and craftsmanship to withstand many of the harshest environments. This highly efficient vaportight is available with LED arrays **rated at 90+ CRI**.

- UL 5VA fiberglass housing will not melt or burn
- Available in 2-foot, 4-foot, or 8-foot lengths with a wide range of outputs ranging from 1,100 to over 23,000 lumens
- Multiple control options - from simple on/off occupancy sensing to advanced network and IoT controls
- Re-boardABILITY prevents obsolescence by ensuring you always have a way to secure the highest efficiency LED modules for your luminaires
- Made in the USA - in our Henderson, NC facility - using mostly domestic and some foreign components. BAA compliant models available

EFFICACY UP TO  
**144.5**  
LUMENS PER WATT

BETTER COLOR RENDERING  
**90+ CRI**  
WITH FOUR CCT OPTIONS

PERFORMANCE AND  
**DURABILITY**  
FOR HARSH ENVIRONMENTS



FOOD PROCESSING



MANUFACTURING



WAREHOUSES



COLD STORAGE

**Voltages available:** 120-277V, 347V

**Size options:** 2', 4', and 8' lengths

**Certifications:** UL 1598 listed for US and Canada, suitable for wet locations. DesignLights Consortium qualified on specific configurations. Other certifications: IP65, IP66, IP67, NEMA 4X, NSF, PSI 1500, RoHS

**Warranty:** 5-year limited system warranty

**Available CCTs:** 3000K 3500K 4000K 5000K

**CRI:** 90+

**Options:** Occupancy sensors, dimming sensors, photocells, network controls, cords, emergency packs, stainless steel latches, multiple hanging options. There are eight different variations of lens options to choose from - in acrylic and polycarbonate



**NVL G2 2'**

**Output:** 1,120 to 6,220 lumens  
**Wattage:** 9.2 to 45.3W



**NVL G2 4'**

**Output:** 2,020 to 11,800 lumens  
**Wattage:** 16.1 to 88.3W




**NVL G2 8'**


**Output:** 4,050 to 23,600 lumens  
**Wattage:** 29.6 to 177.5W



SM




SMBB



SM45

The NVL G2 can be hung with a surface mounting bracket (SM) or a mounting bracket bail (SMBB). The SMBB can be included with a 10' or 20' quick hang cable kit. A 45-degree wall mount bracket (SM45) is available as well.



\*LED lumen packages, efficacy data and lumen output is constantly evolving. Visit [www.lumenfocus.com/nvl](http://www.lumenfocus.com/nvl) for most up-to-date information, spec sheets and photometry files.

