## LED Premium High Bay

The PBL G2 raises the bar for high bay luminaires. This high efficacy premium high bay is a versatile solution for many applications.

- Available in a wide range of lumen output packages and four different sizes
- Multiple controls options to choose from, from standard occupancy sensors to advanced network/IoT controls
- Optional diffuser lenses (pictured) minimize glare and improve aesthetics
- Housing constructed of precision brake-formed aluminum, pre-painted with a highly durable and highly reflective white finish
- Heavy duty ("HD") version available with even more robust construction
- Re-boardABILITY prevents obsolescence by ensuring you always have a way to secure the highest efficiency LED modules for your luminaires
- Made in the USA in our Henderson, NC facility using mostly domestic and some foreign components. BAA Compliant models available

**EFFICACY UP TO** 179.5 **LUMENS PER WATT**  **OUTPUT RANGE** 

11,700 - 53,800

WIDE RANGE OF **OUTPUTS** FOR MAXIMUM VERSATILITY









**Voltages available:** 120-277V, 347V, 480V

**Size options:** 4-foot, 4-foot (wide width), 2-foot, 2-foot (wide width) **Certifications:** UL 1598 listed for US and Canada, suitable for damp locations. DesignLights Consortium qualified on specific configurations. **Warranty:** 5 year limited system warranty. 10-year extended warranty

available on specific products.

Finish options: White (standard), Matte Black, Metallic Silver

**Available CCTs:** 3500K 4000K 5000K

**CRI:** 80

Options: Occupancy sensors, programmable dimming sensors, network controls/loT, cords, emergency packs and more.





Output: 11,000 to 14,160 lumens

Wattage: 71 to 85W

**PBL G2 2W Output:** 16,100 to 24,200 lumens Wattage: 99 to 142W



**Output:** 18,500 to 28,000 lumens Wattage: 115 to 167W



Output: 29,300 to 53,800 lumens Wattage: 181 to 320W















