

PBLA G2

LED Aisle High/Low Bay

The PBLA G2 is an ideal solution for most warehouse aisles and corridors. This high efficacy luminaire is available with a variety of options.

- Enhanced specular reflector is engineered to provide even vertical illumination on shelving and optimize lighting in the aiseways
- Available in a wide range of lumen output packages and four different sizes
- Multiple controls options to choose from, from standard occupancy sensors to advanced network/IoT controls
- Re-boardABILITY prevents obsolescence by ensuring you always have a way to secure the highest efficiency LED modules for your luminaires
- Made in the USA - in our Henderson, NC facility - using mostly domestic and some foreign components. BAA Compliant models available



EFFICACY UP TO
179.2
LUMENS PER WATT

OUTPUT RANGE
7,744 - 56,540
LUMENS

WIDE RANGE OF
OUTPUTS
FOR MAXIMUM VERSATILITY



WAREHOUSES



MANUFACTURING



COLD STORAGE

Voltages available: 120-277V, 347V, 480V
Size options: 4-foot and 8-foot lengths, standard and narrow widths
Certifications: UL 1598 listed for US and Canada, suitable for damp locations. DesignLights Consortium qualified on specific configurations.
Warranty: 5 year limited system warranty. 10-year extended warranty available on specific products.

Available CCTs: 3500K 4000K 5000K

CRI: 80

Options: Occupancy sensors, dimming sensors, photocells, cords, emergency packs, step-down transformers, conformal board coating and more.



PBLA G2 4

Output: 11,180 to 28,270 lumens
Wattage: 66.8 to 171.2W




PBLA G2 8

Output: 29,750 to 56,540 lumens
Wattage: 179.2 to 344.5W



PBLA G2 4N

Output: 7,744 to 14,346 lumens
Wattage: 47.2 to 86.5W



PBLA G2 8N

Output: 11,356 to 28,692 lumens
Wattage: 66.8 to 172.5W



*LED lumen packages, efficacy data and lumen output is constantly evolving. Visit www.lumenfocus.com/pbla for most up-to-date information, spec sheets and photometry files.