



IES ROAD REPORT

PHOTOMETRIC FILENAME : ALK L MD 2 UV 840.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] BLC2012022E-F
[ISSUEDATE] 2020-12-15 17:19
[MANUFAC] LumenFocus, LLC
[LUMCAT] ALK L MD 2 UV 840
[LUMINAIRE] LED Large Area Light
[_VOLTAGE] 120.0 V
[_CURRENT] 1.751A
[_POWERFACTOR] 0.998
[_THD] 4.41
[TESTLAB] Belling Test Laboratory Co., LTD
[_TESTINST] GPM-3000
[_TESTDIST] 14.040 m [K=1.0000]
[_TESTTEMPERATURE] 25.4 'C
[_TESTHUMIDITY]
[_TESTOPERATOR]

CHARACTERISTICS


IES Classification	Type II
Longitudinal Classification	Medium
Lumens Per Lamp	29988.1 (1 lamp)
Total Lamp Lumens	29988.1
Luminaire Lumens	29988
Downward Total Efficiency	100 %
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	143
Total Luminaire Watts	209.74
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	15776.43
Maximum Candela Angle	285H 71V
Maximum Candela (<90 Degrees Vertical)	15776.43
Maximum Candela Angle (<90 Degrees Vertical)	285H 71V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Lamp Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	4950.08 (16.5% Lamp Lumens)
Cutoff Classification (deprecated)	Semi-Cutoff

IES ROAD REPORT
PHOTOMETRIC FILENAME : ALK L MD 2 UV 840.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	4323.6	14.4	14.4
FM - Front-Medium (30-60)	12905.3	43.0	43.0
FH - Front-High (60-80)	5556.7	18.5	18.5
FVH - Front-Very High (80-90)	328.7	1.1	1.1
BL - Back-Low (0-30)	1778.6	5.9	5.9
BM - Back-Medium (30-60)	2960.3	9.9	9.9
BH - Back-High (60-80)	1979.9	6.6	6.6
BVH - Back-Very High (80-90)	155.2	0.5	0.5
UL - Uplight-Low (90-100)	0.0	0.0	0.0
UH - Uplight-High (100-180)	0.0	0.0	0.0
Total	29988.3	99.9	100.0
BUG Rating	B3-U0-G3		


COEFFICIENTS OF UTILIZATION



FLUX DISTRIBUTION


	Lumens	Percent Of Lamp
Downward Street Side	23114.2	77.1
Downward House Side	6873.9	22.9
Downward Total	29988.1	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	29988.1	100.0

POLAR GRAPH




Maximum Candela = 15776.43 Located At Horizontal Angle = 285, Vertical Angle = 71
1 - Vertical Plane Through Horizontal Angles (285 - 105) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (71) (Through Max. Cd.)

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height
 Values Based On 10 Foot Mounting Height
 1/2 Maximum Candela Trace Shown As Dashed Curve
 (+) = Maximum Candela Point

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=4323.6, Medium=12905.3, High=5556.7, Very High=328.7
Back: Low=1778.6, Medium=2960.3, High=1979.9, Very High=155.2
Uplight: Low=0.0, High=0.0

BUG Rating : B3-U0-G3