



## IES ROAD REPORT

PHOTOMETRIC FILENAME : ALK S MD 2 UV 840.IES

### DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002  
[TEST] BLC2012022E-A  
[ISSUE DATE] 2020-12-15 08:52  
[MANUFAC] LumenFocus, LLC  
[LUMCAT] ALK S MD 2 UV 840  
[LUMINAIRE] LED Small Area Light  
[VOLTAGE] 120.0 V  
[CURRENT] 0.567 A  
[POWERFACTOR] 0.998  
[THD] 3.72  
[TESTLAB] Belling Test Laboratory Co., LTD  
[TESTINST] GPM-3000  
[TESTDIST] 14.040 m [K=1.0000]  
[TESTTEMPERATURE] 25.7 °C  
[TESTHUMIDITY]  
[TESTOPERATOR]

### CHARACTERISTICS


IES Classification	Type II
Longitudinal Classification	Medium
Lumens Per Lamp	9445.8 (1 lamp)
Total Lamp Lumens	9445.8
Luminaire Lumens	9446
Downward Total Efficiency	100 %
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	139
Total Luminaire Watts	67.88
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	4588.59
Maximum Candela Angle	285H 69V
Maximum Candela (<90 Degrees Vertical)	4588.59
Maximum Candela Angle (<90 Degrees Vertical)	285H 69V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Lamp Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	1655.92 (17.5% Lamp Lumens)
Cutoff Classification (deprecated)	Semi-Cutoff

**IES ROAD REPORT**  
**PHOTOMETRIC FILENAME : ALK S MD 2 UV 840.IES**

**LUMINAIRE CLASSIFICATION SYSTEM (LCS)**

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	1332.4	14.1	14.1
FM - Front-Medium (30-60)	4057.4	43.0	43.0
FH - Front-High (60-80)	1779.6	18.8	18.8
FVH - Front-Very High (80-90)	92.6	1.0	1.0
BL - Back-Low (0-30)	559.6	5.9	5.9
BM - Back-Medium (30-60)	988.9	10.5	10.5
BH - Back-High (60-80)	594.4	6.3	6.3
BVH - Back-Very High (80-90)	40.8	0.4	0.4
UL - Uplight-Low (90-100)	0.0	0.0	0.0
UH - Uplight-High (100-180)	0.0	0.0	0.0
Total	9445.7	100.0	100.0
BUG Rating	B2-U0-G2		


### COEFFICIENTS OF UTILIZATION



### FLUX DISTRIBUTION


	Lumens	Percent Of Lamp
Downward Street Side	7262.1	76.9
Downward House Side	2183.7	23.1
Downward Total	9445.8	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	9445.8	100.0

POLAR GRAPH




Maximum Candela = 4588.59 Located At Horizontal Angle = 285, Vertical Angle = 69  
# 1 - Vertical Plane Through Horizontal Angles (285 - 105) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (69) (Through Max. Cd.)

## ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:  
Front: Low=1332.4, Medium=4057.4, High=1779.6, Very High=92.6  
Back: Low=559.6, Medium=988.9, High=594.4, Very High=40.8  
Uplight: Low=0.0, High=0.0

BUG Rating : B2-U0-G2