

**Note:** This product has been discontinued and replaced with the LEX v2.



Project: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Cat. #: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Quantity: \_\_\_\_\_

LED

## LEX | LED Exit Sign

### Features:

- Ultra-bright, long life Red or Green LED
- Dual 120/277V
- 4.8V long life, maintenance free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Easy snap-out chevron directional indicators
- Dual-circuit option on the AC-only unit enables it to be connected to two different supplies at the same time, one acting as a back-up to the other
- Custom signs available with custom wording



### Construction:

- Injection molded 5VA flame retardant, high-impact resistant thermoplastic housing

### Mounting:

- Easy snap mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

### Certifications:

- UL listed for damp locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes



### Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 5 yrs.
- see [www.LumenFocus.com](http://www.LumenFocus.com) for complete warranty terms and conditions

### Applications:

For use in dry or damp locations where exit signage is needed.

### Ambient operating Temp.:

0°C to 50°C



Ordering Guide:

example: LEX 2 R DV W-EM SD US

Series	# of Faces	Letter Color	Voltage	Housing Color	Battery	Options
LEX LED Exit	2 Universal Single/ Double Face	R Red  G Green	DV Dual 120/277V	W White  B Black	Blank AC Only  EM Battery Backup	Blank None  SD Self Diagnostics (EM units only)  2C Dual Circuit (AC units only)  US Assembled in the USA  Custom() Custom Wording (specify wording)

Electrical Chart:

Catalog #	Input Watts (W)	Input Watts (W)	Input Amps (A)	Input Amps (A)
	120V	277V	120V	277V
LEX-RED/GREEN/EM/SD/2C	3.8	3.8	0.034	0.020

Schematic:

