



Project: _____
 Location: _____
 Cat. #: _____
 Type: _____
 Quantity: _____

LED

LEX v2 | LED Exit Sign

Features:

- Ultra-bright, long life Red or Green LED
- Dual 120/277V
- 1.2V long life, maintenance free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing

Applications:

For use in dry or damp locations where exit signage is needed.

Ambient operating Temp.:

0°C to 50°C

Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 5 yrs.
- see www.LumenFocus.com for complete warranty terms and conditions

Construction:

- Injection molded 5VA flame retardant, high-impact resistant thermoplastic housing in white or black finish
- Easy snap-out chevron directional indicators

Mounting:

- Easy snap mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

Certifications:

- UL listed for damp locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes
- Certified to CEC under Title 20 Regulations



Ordering Guide:

example: LEX v2 2 R DV W EM SD

Series	# of Faces	Letter Color	Voltage	Housing Color	Battery	Options
LEX v2	2		DV			
LEX v2 LED Exit Version 2	2 Universal Single/ Double Face	R Red G Green	DV Dual 120/277V	W White B Black	Blank AC Only EM Battery Backup	Blank None SD Self Diagnostics (EM units only)

Electrical Chart:

Catalog #	Input Watts (W) 120V	Input Watts (W) 277V	Input Amps (A) 120V	Input Amps (A) 277V
LEX v2 2 R/G EM	1.0	1.0	0.09	0.09
LEX v2 2 R EM SD	2.5	2.5	0.05	0.05
LEX v2 2 G EM SD	2.7	2.7	0.05	0.05

Schematic:

