



Project: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Cat. #: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Quantity: \_\_\_\_\_

LED

## LEXC | LED Exit Sign

### Features:

- Ultra-bright, long life Red or Green LED
- Dual 120/277V
- Bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery)
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing
- 3.6V long life, maintenance free, rechargeable NiCd battery
- 5.5W of remote capacity standard
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination

### Applications:

For use in dry or damp locations where exit signage is needed.

### Ambient operating Temp.:

0°C to 50°C

### Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 5 yrs.
- see [www.LumenFocus.com](http://www.LumenFocus.com) for complete warranty terms and conditions

### Construction:

- Injection molded 5VA flame retardant, high-impact resistant thermoplastic housing in white or black finish
- Easy snap-out chevron directional indicators

### Mounting:

- Easy snap mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

### Certifications:

- UL listed for damp locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes
- Certified to CEC under Title 20 Regulations



Ordering Guide:

example: LEXC 2 R DV W EM RC SD

Series	# of Faces	Letter Color	Voltage	Housing Color	Battery	Remote Capacity	Options
LEXC	2		DV		EM	RC	
<b>LEXC</b> LED Exit	<b>2</b> Universal Single/ Double Face	<b>R</b> Red <b>G</b> Green	<b>DV</b> Dual 120/277V	<b>W</b> White <b>B</b> Black	<b>EM</b> Battery Backup	<b>RC</b> 5.5W Remote Capacity (Standard)	<b>Blank</b> None <b>SD</b> Self Diagnostics

Schematic:

