



Project: _____
 Location: _____
 Cat. #: _____
 Type: _____
 Quantity: _____

LED

LEXH | Hazardous Location LED Exit Sign

Features:

- Ultra-bright, long life Red or Green LED
- Dual 120/277V
- 4.8V long life, maintenance free, rechargeable NiCd battery (EM models)
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Bi-color LED indicator light alerts occupants on battery condition (Green-normal, Red-check battery)
- Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing

Construction:

- Housing is fiberglass reinforced polycarbonate construction in gray finish
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws
- Field selectable steel knockout chevron directional indicators

Mounting:

- Die-cast mounting brackets included for surface wall mount installation
- Pre-installed conduit hub for conduit and pendant mount installations

Ambient operating Temp.:

- -20°C to 50°C

Certifications:

- UL listed for wet locations
- Rated for Class I, Division 2, Groups A, B, C, D
- IP66 rated
- UL924
- UL844
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes



Warranty:

- 5 year limited warranty on housing and electronics. Battery prorated for 5 yrs.
- see www.LumenFocus.com for complete warranty terms and conditions



Ordering Guide:

example: LEXH 2 R DV G EM SD TP

Series	# of Faces	Letter Color	Voltage	Housing Color	Battery	Options
LEXH			DV	G		
LEXH Hazardous Location Exit Sign	1 Single Face	R Red	DV Dual 120/277V	G Gray	Blank AC Only	Blank None
	2 Double Face	G Green			EM Battery Backup	SD Self Diagnostics ⁽¹⁾

Notes

⁽¹⁾ Available on EM units only

Schematic:

