



Project: _____
 Location: _____
 Cat. #: _____
 Type: _____
 Quantity: _____

LED

LEXRM | LED Running Man Exit Sign

Features:

- Ultra-bright, long life LED exit sign illumination
- Dual 120/347V
- 9.6V long life, maintenance free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing

Applications:

For use in dry or damp locations where exit signage is needed.

Mounting:

- Easy snap mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

Ambient operating Temp.:

0°C to 50°C

Construction:

- Injection molded 5VA flame retardant, high-impact resistant thermoplastic housing in white or black finish
- Field selectable, universal directional indication provided with three (Left, Right, and No Arrow) pictogram legends

Certifications:

- CSA listed for damp locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes
- Meets or exceeds CSA C22.2 No. 141.10 standard requirements for Emergency lighting equipment



Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 5 yrs.
- see www.LumenFocus.com for complete warranty terms and conditions



Ordering Guide:

example: LEXRM 2 12/34 W EM SD

Series	# of Faces	Voltage	Housing Color	Battery	Options
LEXRM	2	12/34			
LEXRM LED Running Man Exit Sign	2 Universal Single/ Double Face	12/34 Dual 120/347V	W White B Black	Blank AC Only EM Battery Backup	Blank None SD Self Diagnostics (EM units only)

Electrical Chart:

Catalog #	Input Watts (W) 120V	Input Watts (W) 347V	Input Amps (A) 120V	Input Amps (A) 347V
LEXRM	4.4	4.4	0.037	0.013

Schematic:

