





MREMS | MR-16 LED Emergency Unit

Features:

- Fully adjustable, ultra-bright, long life 3.6W MR-16 base LED lamp heads for optimized center-to-center spacing
- Optional 7.0W high-lumen heads available for increased center to center spacing
- Dual 120/277V
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing
- Low voltage disconnect prevents battery from deep discharge
- 6V maintenance-free, rechargeable sealed lead acid battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours

Applications:

Suitable for wall mount in dry or damp locations where emergency lighting is needed

Ambient operating Temp.: 20°C to 40°C

Construction:

 Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish

Mounting:

- Universal knockout pattern on back plate for wall mount. Snaps into place making internal electrical connections
- Knockout for conduit applications

Certifications:

- UL listed for damp locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes



Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 2 yrs.
- see <u>www.LumenFocus.com</u> for complete warranty terms and conditions





Ordering Guide:

Series	Voltage	Housing Color	Options
MREMS	DV		
MREMS MR-16 LED Emergency Unit	DV Dual 120/277V	W White	Blank None
		B Black	HL High Lumen 7.0W LED
			Lamps US
			Assembled in USA

Schematic:



