



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 2 SEL45 UV FR 935 @850MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-013(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/5/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL G2 2 SEL45 UV FR 935

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] One LS3872A 84 LED board, 3500K

[BALLAST] One KTLD-45-UV-PS850-54-VDIM-LM1 LED driver set to 850mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5494
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	146
Total Luminaire Watts	37.6
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	1.99 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	22793	22203	22410
55	19561	20030	20585
65	15429	17387	18209
75	10956	14703	15491
85	5752	13386	13709

**IES INDOOR REPORT****PHOTOMETRIC FILENAME : ECL G2 2 SEL45 UV FR 935 @850MA.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	684.85	N.A.	12.50
0-30	1455.95	N.A.	26.50
0-40	2382.81	N.A.	43.40
0-60	4170.88	N.A.	75.90
0-80	5194.21	N.A.	94.50
0-90	5393.31	N.A.	98.20
10-90	5216.38	N.A.	94.90
20-40	1697.97	N.A.	30.90
20-50	2647.64	N.A.	48.20
40-70	2417.81	N.A.	44.00
60-80	1023.33	N.A.	18.60
70-80	393.59	N.A.	7.20
80-90	199.10	N.A.	3.60
90-110	100.54	N.A.	1.80
90-120	100.84	N.A.	1.80
90-130	100.84	N.A.	1.80
90-150	100.84	N.A.	1.80
90-180	100.84	N.A.	1.80
110-180	0.30	N.A.	0.00
0-180	5494.15	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	176.93
10-20	507.92
20-30	771.10
30-40	926.86
40-50	949.68
50-60	838.39
60-70	629.74
70-80	393.59
80-90	199.10
90-100	81.09
100-110	19.45
110-120	0.30
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 2 SEL45 UV FR 935 @850MA.IES

## COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	44	39	49	43	39	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	37	31	43	36	31	41	35	31	29
9	56	42	34	29	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	26	36	30	25	35	29	25	23

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 2 SEL45 UV FR 935 @850MA.IES

## UGR TABLE - CORRECTED


### Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	21.2	22.8	21.6	23.2	23.6	22.9	24.5	23.3	24.9	25.3
	3H	22.5	24.0	22.9	24.3	24.7	24.9	26.4	25.3	26.7	27.1
	4H	22.9	24.3	23.3	24.7	25.1	25.7	27.1	26.2	27.5	27.9
	6H	23.1	24.4	23.6	24.8	25.2	26.5	27.8	27.0	28.2	28.6
	8H	23.2	24.4	23.6	24.8	25.3	26.9	28.1	27.3	28.5	29.0
	12H	23.2	24.4	23.7	24.8	25.3	27.2	28.4	27.7	28.8	29.3
4H	2H	22.1	23.4	22.5	23.8	24.3	23.4	24.8	23.8	25.2	25.6
	3H	23.6	24.8	24.0	25.2	25.6	25.6	26.8	26.0	27.2	27.7
	4H	24.1	25.2	24.6	25.6	26.1	26.6	27.7	27.1	28.1	28.6
	6H	24.4	25.4	24.9	25.9	26.4	27.5	28.5	28.0	29.0	29.5
	8H	24.5	25.4	25.0	25.9	26.4	28.0	28.9	28.5	29.3	29.8
	12H	24.6	25.4	25.1	25.9	26.4	28.4	29.2	29.0	29.8	30.3
8H	4H	24.7	25.5	25.1	26.0	26.5	26.8	27.7	27.3	28.2	28.7
	6H	25.2	25.9	25.7	26.4	26.9	27.9	28.7	28.5	29.2	29.7
	8H	25.3	26.0	25.9	26.5	27.1	28.5	29.2	29.1	29.7	30.2
	12H	25.4	26.0	26.0	26.6	27.2	29.1	29.7	29.7	30.2	30.8
12H	4H	24.8	25.6	25.3	26.1	26.6	26.8	27.6	27.3	28.1	28.6
	6H	25.4	26.1	25.9	26.5	27.1	28.0	28.7	28.6	29.2	29.7
	8H	25.6	26.2	26.2	26.7	27.3	28.6	29.2	29.2	29.7	30.3

Maximum UGR = 30.8

POLAR GRAPH



Maximum Candela = 1870.735 Located At Horizontal Angle = 90, Vertical Angle = 1.5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (1.5) (Through Max. Cd.)