



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 6 SEL100 UV FR 930 @1500MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-018(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/5/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL G2 6 SEL100 UV FR 930

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Three LS3872A 68 LED boards, 3000K

[BALLAST] One KTLD-100-UV-PS1800-54-VDIM-LM2 LED driver set to 1500mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	11257
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	152
Total Luminaire Watts	74.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	6.00 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	15891	15269	15205
55	13881	13873	13965
65	11197	12153	12328
75	8189	10418	10437
85	4857	9771	9155

**IES INDOOR REPORT****PHOTOMETRIC FILENAME : ECL G2 6 SEL100 UV FR 930 @1500MA.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	1399.55	N.A.	12.40
0-30	2976.29	N.A.	26.40
0-40	4873.37	N.A.	43.30
0-60	8542.69	N.A.	75.90
0-80	10648.96	N.A.	94.60
0-90	11056.01	N.A.	98.20
10-90	10694.62	N.A.	95.00
20-40	3473.82	N.A.	30.90
20-50	5420.36	N.A.	48.20
40-70	4966.32	N.A.	44.10
60-80	2106.27	N.A.	18.70
70-80	809.28	N.A.	7.20
80-90	407.05	N.A.	3.60
90-110	200.66	N.A.	1.80
90-120	201.06	N.A.	1.80
90-130	201.06	N.A.	1.80
90-150	201.06	N.A.	1.80
90-180	201.06	N.A.	1.80
110-180	0.41	N.A.	0.00
0-180	11257.08	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	361.40
10-20	1038.16
20-30	1576.74
30-40	1897.08
40-50	1946.55
50-60	1722.78
60-70	1296.99
70-80	809.28
80-90	407.05
90-100	163.17
100-110	37.49
110-120	0.41
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 6 SEL100 UV FR 930 @1500MA.IES

## COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	49	43	38	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	36	31	42	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL G2 6 SEL100 UV FR 930 @1500MA.IES**

**UGR TABLE - CORRECTED**

Reflectances											
Ceiling Cavity		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
Floor Cavity		20	20	20	20	20	20	20	20	20	20
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	20.0	21.6	20.4	22.0	22.3	21.7	23.3	22.1	23.7	24.0
	3H	21.3	22.8	21.7	23.1	23.5	23.7	25.1	24.1	25.5	25.9
	4H	21.7	23.1	22.1	23.5	23.9	24.5	25.9	25.0	26.3	26.7
	6H	21.9	23.2	22.4	23.6	24.0	25.3	26.6	25.8	27.0	27.5
	8H	22.0	23.2	22.4	23.6	24.1	25.7	26.9	26.2	27.4	27.8
	12H	22.0	23.2	22.5	23.6	24.1	26.1	27.3	26.6	27.7	28.2
4H	2H	20.8	22.2	21.3	22.6	23.0	22.2	23.5	22.6	23.9	24.4
	3H	22.4	23.5	22.8	24.0	24.4	24.4	25.5	24.8	26.0	26.4
	4H	22.9	24.0	23.4	24.4	24.9	25.4	26.4	25.9	26.9	27.4
	6H	23.3	24.2	23.7	24.7	25.2	26.4	27.3	26.8	27.8	28.3
	8H	23.3	24.2	23.8	24.7	25.2	26.8	27.7	27.3	28.2	28.7
	12H	23.4	24.2	23.9	24.7	25.2	27.3	28.1	27.8	28.6	29.1
8H	4H	23.5	24.3	24.0	24.8	25.3	25.6	26.5	26.1	27.0	27.5
	6H	24.0	24.7	24.5	25.2	25.8	26.8	27.5	27.3	28.0	28.5
	8H	24.2	24.8	24.7	25.4	25.9	27.4	28.0	27.9	28.5	29.1
	12H	24.3	24.9	24.8	25.4	26.0	28.0	28.6	28.5	29.1	29.7
12H	4H	23.6	24.4	24.1	24.9	25.4	25.6	26.4	26.1	26.9	27.4
	6H	24.2	24.9	24.8	25.4	25.9	26.8	27.5	27.4	28.0	28.6
	8H	24.4	25.0	25.0	25.6	26.2	27.5	28.0	28.0	28.6	29.2

Maximum UGR = 29.7

POLAR GRAPH



Maximum Candela = 3825.366 Located At Horizontal Angle = 90, Vertical Angle = 3.5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (3.5) (Through Max. Cd.)