



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 6 SEL15 UV FR 935 @200MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-018(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/5/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL G2 6 SEL15 UV FR 935

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Three LS3872A 28 LED boards, 3500K

[BALLAST] One KTLD-15-UV-PS300-54-VDIM-LP1 LED driver set to 200mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1324
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	149
Total Luminaire Watts	8.9
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	6.00 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1869	1796	1788
55	1632	1631	1642
65	1317	1429	1450
75	963	1225	1227
85	571	1149	1077

**IES INDOOR REPORT****PHOTOMETRIC FILENAME : ECL G2 6 SEL15 UV FR 935 @200MA.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	164.58	N.A.	12.40
0-30	349.99	N.A.	26.40
0-40	573.07	N.A.	43.30
0-60	1004.56	N.A.	75.90
0-80	1252.24	N.A.	94.60
0-90	1300.11	N.A.	98.20
10-90	1257.61	N.A.	95.00
20-40	408.50	N.A.	30.90
20-50	637.40	N.A.	48.20
40-70	584.00	N.A.	44.10
60-80	247.68	N.A.	18.70
70-80	95.17	N.A.	7.20
80-90	47.87	N.A.	3.60
90-110	23.60	N.A.	1.80
90-120	23.64	N.A.	1.80
90-130	23.64	N.A.	1.80
90-150	23.64	N.A.	1.80
90-180	23.64	N.A.	1.80
110-180	0.05	N.A.	0.00
0-180	1323.76	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	42.50
10-20	122.08
20-30	185.41
30-40	223.08
40-50	228.90
50-60	202.59
60-70	152.52
70-80	95.17
80-90	47.87
90-100	19.19
100-110	4.41
110-120	0.05
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 6 SEL15 UV FR 935 @200MA.IES

## COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	49	43	38	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	36	31	42	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 6 SEL15 UV FR 935 @200MA.IES

## UGR TABLE - CORRECTED


### Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	12.6	14.2	13.0	14.6	14.9	14.3	15.9	14.7	16.3	16.6
	3H	13.9	15.4	14.3	15.7	16.1	16.3	17.7	16.7	18.1	18.5
	4H	14.3	15.7	14.7	16.1	16.5	17.1	18.5	17.6	18.9	19.3
	6H	14.5	15.8	15.0	16.2	16.6	17.9	19.2	18.4	19.6	20.0
	8H	14.6	15.8	15.0	16.2	16.7	18.3	19.5	18.8	20.0	20.4
	12H	14.6	15.8	15.1	16.2	16.7	18.7	19.9	19.2	20.3	20.8
4H	2H	13.4	14.8	13.9	15.2	15.6	14.8	16.1	15.2	16.5	17.0
	3H	15.0	16.1	15.4	16.6	17.0	17.0	18.1	17.4	18.6	19.0
	4H	15.5	16.6	16.0	17.0	17.5	18.0	19.0	18.5	19.5	20.0
	6H	15.8	16.8	16.3	17.3	17.8	19.0	19.9	19.4	20.4	20.9
	8H	15.9	16.8	16.4	17.3	17.8	19.4	20.3	19.9	20.8	21.3
	12H	16.0	16.8	16.5	17.3	17.8	19.9	20.7	20.4	21.2	21.7
8H	4H	16.1	16.9	16.5	17.4	17.9	18.2	19.1	18.7	19.6	20.1
	6H	16.6	17.3	17.1	17.8	18.4	19.4	20.1	19.9	20.6	21.1
	8H	16.8	17.4	17.3	18.0	18.5	20.0	20.6	20.5	21.1	21.7
	12H	16.9	17.5	17.4	18.0	18.6	20.6	21.2	21.1	21.7	22.3
12H	4H	16.2	17.0	16.7	17.5	18.0	18.2	19.0	18.7	19.5	20.0
	6H	16.8	17.5	17.4	18.0	18.5	19.4	20.1	20.0	20.6	21.2
	8H	17.0	17.6	17.6	18.2	18.8	20.1	20.6	20.6	21.2	21.8

Maximum UGR = 22.3

POLAR GRAPH



Maximum Candela = 449.837 Located At Horizontal Angle = 90, Vertical Angle = 3.5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (3.5) (Through Max. Cd.)