



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 6 SEL75 UV FR 940 @1400MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-018(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/5/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL G2 6 SEL75 UV FR 940

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Three LS3872A 48 LED boards, 4000K

[BALLAST] One KTLD-75-UV-PS1400-54-VDIM-LM2 LED driver set to 1400mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	10604
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	151
Total Luminaire Watts	70.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	6.00 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	14969	14383	14323
55	13075	13068	13155
65	10547	11447	11612
75	7714	9814	9831
85	4576	9204	8624

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL G2 6 SEL75 UV FR 940 @1400MA.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	1318.35	N.A.	12.40
0-30	2803.6	N.A.	26.40
0-40	4590.6	N.A.	43.30
0-60	8047.02	N.A.	75.90
0-80	10031.08	N.A.	94.60
0-90	10414.51	N.A.	98.20
10-90	10074.08	N.A.	95.00
20-40	3272.25	N.A.	30.90
20-50	5105.86	N.A.	48.20
40-70	4678.16	N.A.	44.10
60-80	1984.06	N.A.	18.70
70-80	762.32	N.A.	7.20
80-90	383.43	N.A.	3.60
90-110	189.01	N.A.	1.80
90-120	189.40	N.A.	1.80
90-130	189.40	N.A.	1.80
90-150	189.40	N.A.	1.80
90-180	189.40	N.A.	1.80
110-180	0.38	N.A.	0.00
0-180	10603.91	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	340.43
10-20	977.92
20-30	1485.25
30-40	1787.00
40-50	1833.6
50-60	1622.82
60-70	1221.74
70-80	762.32
80-90	383.43
90-100	153.70
100-110	35.31
110-120	0.38
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL G2 6 SEL75 UV FR 940 @1400MA.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	49	43	38	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	36	31	42	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL G2 6 SEL75 UV FR 940 @1400MA.IES**

**UGR TABLE - CORRECTED**


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	19.8	21.4	20.2	21.8	22.1	21.5	23.1	21.9	23.5	23.8
	3H	21.1	22.6	21.5	22.9	23.3	23.5	24.9	23.9	25.3	25.7
	4H	21.5	22.9	21.9	23.3	23.7	24.3	25.7	24.8	26.1	26.5
	6H	21.7	23.0	22.2	23.4	23.8	25.1	26.4	25.6	26.8	27.3
	8H	21.8	23.0	22.2	23.4	23.9	25.5	26.7	26.0	27.2	27.6
	12H	21.8	23.0	22.3	23.4	23.9	25.9	27.1	26.4	27.5	28.0
4H	2H	20.6	22.0	21.1	22.4	22.8	22.0	23.3	22.4	23.7	24.2
	3H	22.2	23.3	22.6	23.8	24.2	24.2	25.3	24.6	25.8	26.2
	4H	22.7	23.8	23.2	24.2	24.7	25.2	26.2	25.7	26.7	27.2
	6H	23.1	24.0	23.5	24.5	25.0	26.2	27.1	26.6	27.6	28.1
	8H	23.1	24.0	23.6	24.5	25.0	26.6	27.5	27.1	28.0	28.5
	12H	23.2	24.0	23.7	24.5	25.0	27.1	27.9	27.6	28.4	28.9
8H	4H	23.3	24.1	23.8	24.6	25.1	25.4	26.3	25.9	26.8	27.3
	6H	23.8	24.5	24.3	25.0	25.6	26.6	27.3	27.1	27.8	28.3
	8H	24.0	24.6	24.5	25.2	25.7	27.2	27.8	27.7	28.3	28.9
	12H	24.1	24.7	24.6	25.2	25.8	27.8	28.4	28.3	28.9	29.5
12H	4H	23.4	24.2	23.9	24.7	25.2	25.4	26.2	25.9	26.7	27.2
	6H	24.0	24.7	24.6	25.2	25.7	26.6	27.3	27.2	27.8	28.4
	8H	24.2	24.8	24.8	25.4	26.0	27.3	27.8	27.8	28.4	29.0

Maximum UGR = 29.5

POLAR GRAPH



Maximum Candela = 3603.406 Located At Horizontal Angle = 90, Vertical Angle = 3.5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (3.5) (Through Max. Cd.)