



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 8 SEL15 UV FR 940 @230MA.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-018(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/5/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL G2 8 SEL15 UV FR 940

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Four LS3872A 28 LED boards, 4000K

[BALLAST] One KTLD-15-UV-PS300-54-VDIM-LP1 LED driver set to 230mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

| | |
|---------------------------------|---------------------|
| Lumens Per Lamp | N.A. (absolute) |
| Total Lamp Lumens | N.A. (absolute) |
| Luminaire Lumens | 1555 |
| Total Luminaire Efficiency | N.A. |
| Luminaire Efficacy Rating (LER) | 152 |
| Total Luminaire Watts | 10.2 |
| Ballast Factor | 1.00 |
| CIE Type | Direct |
| Spacing Criterion (0-180) | 1.26 |
| Spacing Criterion (90-270) | 1.30 |
| Spacing Criterion (Diagonal) | 1.38 |
| Basic Luminous Shape | Rectangular w/Sides |
| Luminous Length (0-180) | 8.00 ft |
| Luminous Width (90-270) | 0.38 ft |
| Luminous Height | 0.06 ft |

LUMINANCE DATA (cd/sq.m)

| Angle In Degrees | Average 0-Deg | Average 45-Deg | Average 90-Deg |
|---------------------|------------------|-------------------|-------------------|
| 45 | 1651 | 1585 | 1575 |
| 55 | 1444 | 1441 | 1447 |
| 65 | 1166 | 1263 | 1277 |
| 75 | 857 | 1085 | 1081 |
| 85 | 517 | 1021 | 949 |

IES INDOOR REPORT**PHOTOMETRIC FILENAME : ECL G2 8 SEL15 UV FR 940 @230MA.IES****ZONAL LUMEN SUMMARY**

| Zone | Lumens | %Lamp | %Fixt |
|---------|---------|-------|--------|
| 0-20 | 193.34 | N.A. | 12.40 |
| 0-30 | 411.16 | N.A. | 26.40 |
| 0-40 | 673.23 | N.A. | 43.30 |
| 0-60 | 1180.13 | N.A. | 75.90 |
| 0-80 | 1471.09 | N.A. | 94.60 |
| 0-90 | 1527.33 | N.A. | 98.20 |
| 10-90 | 1477.4 | N.A. | 95.00 |
| 20-40 | 479.89 | N.A. | 30.90 |
| 20-50 | 748.79 | N.A. | 48.20 |
| 40-70 | 686.07 | N.A. | 44.10 |
| 60-80 | 290.97 | N.A. | 18.70 |
| 70-80 | 111.80 | N.A. | 7.20 |
| 80-90 | 56.23 | N.A. | 3.60 |
| 90-110 | 27.72 | N.A. | 1.80 |
| 90-120 | 27.78 | N.A. | 1.80 |
| 90-130 | 27.78 | N.A. | 1.80 |
| 90-150 | 27.78 | N.A. | 1.80 |
| 90-180 | 27.78 | N.A. | 1.80 |
| 110-180 | 0.06 | N.A. | 0.00 |
| 0-180 | 1555.1 | N.A. | 100.00 |

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

| Zone | Lumens |
|---------|--------|
| 0-10 | 49.92 |
| 10-20 | 143.42 |
| 20-30 | 217.82 |
| 30-40 | 262.07 |
| 40-50 | 268.90 |
| 50-60 | 237.99 |
| 60-70 | 179.17 |
| 70-80 | 111.80 |
| 80-90 | 56.23 |
| 90-100 | 22.54 |
| 100-110 | 5.18 |
| 110-120 | 0.06 |
| 120-130 | 0.00 |
| 130-140 | 0.00 |
| 140-150 | 0.00 |
| 150-160 | 0.00 |
| 160-170 | 0.00 |
| 170-180 | 0.00 |

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 8 SEL15 UV FR 940 @230MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

| RC | 80 | | | | 70 | | | | 50 | | | 30 | | | 10 | | | 0 |
|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 110 | 110 | 110 | 105 | 105 | 105 | 100 | 100 | 100 | 98 |
| 1 | 108 | 103 | 98 | 94 | 105 | 100 | 96 | 92 | 95 | 92 | 89 | 91 | 88 | 86 | 87 | 85 | 83 | 81 |
| 2 | 98 | 89 | 82 | 76 | 95 | 87 | 81 | 75 | 83 | 78 | 73 | 80 | 75 | 71 | 76 | 73 | 69 | 67 |
| 3 | 89 | 78 | 70 | 63 | 86 | 77 | 69 | 63 | 73 | 67 | 61 | 70 | 65 | 60 | 67 | 63 | 59 | 56 |
| 4 | 82 | 69 | 60 | 54 | 79 | 68 | 60 | 53 | 65 | 58 | 52 | 63 | 56 | 51 | 60 | 55 | 50 | 48 |
| 5 | 75 | 62 | 53 | 46 | 73 | 61 | 52 | 46 | 58 | 51 | 45 | 56 | 50 | 44 | 54 | 48 | 44 | 42 |
| 6 | 69 | 56 | 47 | 40 | 67 | 55 | 46 | 40 | 53 | 45 | 39 | 51 | 44 | 39 | 49 | 43 | 38 | 36 |
| 7 | 64 | 51 | 42 | 36 | 62 | 50 | 41 | 35 | 48 | 40 | 35 | 46 | 40 | 35 | 45 | 39 | 34 | 32 |
| 8 | 60 | 46 | 38 | 32 | 58 | 45 | 37 | 32 | 44 | 36 | 31 | 42 | 36 | 31 | 41 | 35 | 31 | 29 |
| 9 | 56 | 42 | 34 | 28 | 54 | 42 | 34 | 28 | 40 | 33 | 28 | 39 | 33 | 28 | 38 | 32 | 28 | 26 |
| 10 | 52 | 39 | 31 | 26 | 51 | 38 | 31 | 26 | 37 | 30 | 26 | 36 | 30 | 25 | 35 | 29 | 25 | 23 |

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 8 SEL15 UV FR 940 @230MA.IES

UGR TABLE - CORRECTED


Reflectances

| | | | | | | | | | | |
|----------------|----|----|----|----|----|----|----|----|----|----|
| Ceiling Cavity | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 |
| Walls | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 |
| Floor Cavity | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |

| Room Size | | UGR Viewed Crosswise | | | | | UGR Viewed Endwise | | | | |
|-----------|------|----------------------|------|------|------|------|--------------------|------|------|------|------|
| X=2H | Y=2H | 12.1 | 13.7 | 12.5 | 14.1 | 14.4 | 13.8 | 15.4 | 14.2 | 15.8 | 16.1 |
| | 3H | 13.4 | 14.9 | 13.8 | 15.2 | 15.6 | 15.8 | 17.3 | 16.2 | 17.6 | 18.0 |
| | 4H | 13.8 | 15.2 | 14.2 | 15.6 | 16.0 | 16.6 | 18.0 | 17.1 | 18.4 | 18.8 |
| | 6H | 14.0 | 15.3 | 14.5 | 15.7 | 16.2 | 17.4 | 18.7 | 17.9 | 19.1 | 19.6 |
| | 8H | 14.1 | 15.3 | 14.5 | 15.7 | 16.2 | 17.8 | 19.1 | 18.3 | 19.5 | 19.9 |
| | 12H | 14.1 | 15.3 | 14.6 | 15.7 | 16.2 | 18.2 | 19.4 | 18.7 | 19.8 | 20.3 |
| 4H | 2H | 12.9 | 14.3 | 13.4 | 14.7 | 15.1 | 14.3 | 15.7 | 14.7 | 16.0 | 16.5 |
| | 3H | 14.5 | 15.7 | 14.9 | 16.1 | 16.5 | 16.5 | 17.7 | 16.9 | 18.1 | 18.5 |
| | 4H | 15.0 | 16.1 | 15.5 | 16.5 | 17.0 | 17.5 | 18.6 | 18.0 | 19.0 | 19.5 |
| | 6H | 15.4 | 16.3 | 15.8 | 16.8 | 17.3 | 18.5 | 19.4 | 19.0 | 19.9 | 20.4 |
| | 8H | 15.4 | 16.3 | 15.9 | 16.8 | 17.3 | 19.0 | 19.8 | 19.4 | 20.3 | 20.8 |
| | 12H | 15.5 | 16.3 | 16.0 | 16.8 | 17.3 | 19.5 | 20.2 | 20.0 | 20.8 | 21.3 |
| 8H | 4H | 15.6 | 16.4 | 16.1 | 16.9 | 17.4 | 17.7 | 18.6 | 18.2 | 19.1 | 19.6 |
| | 6H | 16.1 | 16.8 | 16.6 | 17.3 | 17.9 | 18.9 | 19.6 | 19.4 | 20.1 | 20.7 |
| | 8H | 16.3 | 16.9 | 16.8 | 17.5 | 18.0 | 19.5 | 20.1 | 20.0 | 20.7 | 21.2 |
| | 12H | 16.4 | 17.0 | 16.9 | 17.5 | 18.1 | 20.1 | 20.7 | 20.7 | 21.2 | 21.9 |
| 12H | 4H | 15.7 | 16.5 | 16.2 | 17.0 | 17.5 | 17.7 | 18.5 | 18.3 | 19.1 | 19.6 |
| | 6H | 16.3 | 17.0 | 16.9 | 17.5 | 18.1 | 19.0 | 19.6 | 19.5 | 20.1 | 20.7 |
| | 8H | 16.6 | 17.1 | 17.1 | 17.7 | 18.3 | 19.6 | 20.2 | 20.1 | 20.7 | 21.3 |

Maximum UGR = 21.9

POLAR GRAPH



Maximum Candela = 528.453 Located At Horizontal Angle = 90, Vertical Angle = 3.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (3.5) (Through Max. Cd.)