



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 8 SEL100 UV FR 935 @1600MA.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-018(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/5/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL G2 8 SEL100 UV FR 935

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Four LS3872A 48 LED boards, 3500K

[BALLAST] One KTLD-100-UV-PS1800-54-VDIM-LM2 LED driver set to 1600mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	12008
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	151
Total Luminaire Watts	79.5
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.26
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	8.00 ft
Luminous Width (90-270)	0.38 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	12746	12236	12164
55	11146	11123	11172
65	9007	9753	9862
75	6614	8374	8350
85	3993	7885	7324

IES INDOOR REPORT**PHOTOMETRIC FILENAME : ECL G2 8 SEL100 UV FR 935 @1600MA.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	1492.88	N.A.	12.40
0-30	3174.76	N.A.	26.40
0-40	5198.34	N.A.	43.30
0-60	9112.34	N.A.	75.90
0-80	11359.06	N.A.	94.60
0-90	11793.26	N.A.	98.20
10-90	11407.77	N.A.	95.00
20-40	3705.46	N.A.	30.90
20-50	5781.81	N.A.	48.20
40-70	5297.49	N.A.	44.10
60-80	2246.72	N.A.	18.70
70-80	863.24	N.A.	7.20
80-90	434.20	N.A.	3.60
90-110	214.04	N.A.	1.80
90-120	214.47	N.A.	1.80
90-130	214.47	N.A.	1.80
90-150	214.47	N.A.	1.80
90-180	214.47	N.A.	1.80
110-180	0.43	N.A.	0.00
0-180	12007.73	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	385.49
10-20	1107.38
20-30	1681.88
30-40	2023.58
40-50	2076.35
50-60	1837.66
60-70	1383.48
70-80	863.24
80-90	434.20
90-100	174.05
100-110	39.99
110-120	0.43
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL G2 8 SEL100 UV FR 935 @1600MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	108	103	98	94	105	100	96	92	95	92	89	91	88	86	87	85	83	81
2	98	89	82	76	95	87	81	75	83	78	73	80	75	71	76	73	69	67
3	89	78	70	63	86	77	69	63	73	67	61	70	65	60	67	63	59	56
4	82	69	60	54	79	68	60	53	65	58	52	63	56	51	60	55	50	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	54	48	44	42
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	49	43	38	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32
8	60	46	38	32	58	45	37	32	44	36	31	42	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23


IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL G2 8 SEL100 UV FR 935 @1600MA.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	19.2	20.8	19.6	21.2	21.5	20.9	22.5	21.3	22.9	23.2
	3H	20.5	22.0	20.9	22.3	22.7	22.9	24.4	23.3	24.7	25.1
	4H	20.9	22.3	21.3	22.7	23.1	23.7	25.1	24.2	25.5	25.9
	6H	21.1	22.4	21.6	22.8	23.3	24.5	25.8	25.0	26.2	26.7
	8H	21.2	22.4	21.6	22.8	23.3	24.9	26.2	25.4	26.6	27.0
	12H	21.2	22.4	21.7	22.8	23.3	25.3	26.5	25.8	26.9	27.4
4H	2H	20.0	21.4	20.5	21.8	22.2	21.4	22.8	21.8	23.1	23.6
	3H	21.6	22.8	22.0	23.2	23.6	23.6	24.8	24.0	25.2	25.6
	4H	22.1	23.2	22.6	23.6	24.1	24.6	25.7	25.1	26.1	26.6
	6H	22.5	23.4	22.9	23.9	24.4	25.6	26.5	26.1	27.0	27.5
	8H	22.5	23.4	23.0	23.9	24.4	26.0	26.9	26.5	27.4	27.9
	12H	22.6	23.4	23.1	23.9	24.4	26.6	27.3	27.1	27.9	28.4
8H	4H	22.7	23.5	23.2	24.0	24.5	24.8	25.7	25.3	26.2	26.7
	6H	23.2	23.9	23.7	24.4	25.0	26.0	26.7	26.5	27.2	27.8
	8H	23.4	24.0	23.9	24.6	25.1	26.6	27.2	27.1	27.8	28.3
	12H	23.5	24.1	24.0	24.6	25.2	27.2	27.8	27.8	28.3	28.9
12H	4H	22.8	23.6	23.3	24.1	24.6	24.8	25.6	25.4	26.2	26.7
	6H	23.4	24.1	24.0	24.6	25.2	26.1	26.7	26.6	27.2	27.8
	8H	23.7	24.2	24.2	24.8	25.4	26.7	27.3	27.2	27.8	28.4

Maximum UGR = 28.9

POLAR GRAPH



Maximum Candela = 4080.452 Located At Horizontal Angle = 90, Vertical Angle = 3.5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (3.5) (Through Max. Cd.)