



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 2 SEL45 UV FR 930 @700MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-003(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/6/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL N G2 2 SEL45 UV FR 930

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] One LS3872A 84 LED board, 3000K

[BALLAST] One KTLD-45-UV-PS850-54-VDIM-LM1 LED driver set at 700mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4530
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	149
Total Luminaire Watts	30.5
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	1.99 ft
Luminous Width (90-270)	0.21 ft
Luminous Height	0.06 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	32696	29877	29490
55	28001	26169	26125
65	22197	21860	22158
75	15934	17527	17715
85	8804	14215	13961

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : ECL N G2 2 SEL45 UV FR 930 @700MA.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	553.82	N.A.	12.20
0-30	1178.27	N.A.	26.00
0-40	1928.39	N.A.	42.60
0-60	3370.42	N.A.	74.40
0-80	4202.13	N.A.	92.80
0-90	4369.89	N.A.	96.50
10-90	4226.92	N.A.	93.30
20-40	1374.57	N.A.	30.30
20-50	2141.12	N.A.	47.30
40-70	1951.37	N.A.	43.10
60-80	831.71	N.A.	18.40
70-80	322.37	N.A.	7.10
80-90	167.76	N.A.	3.70
90-110	116.02	N.A.	2.60
90-120	136.06	N.A.	3.00
90-130	147.07	N.A.	3.20
90-150	156.94	N.A.	3.50
90-180	159.70	N.A.	3.50
110-180	43.68	N.A.	1.00
0-180	4529.6	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	142.97
10-20	410.85
20-30	624.46
30-40	750.11
40-50	766.55
50-60	675.48
60-70	509.34
70-80	322.37
80-90	167.76
90-100	77.95
100-110	38.07
110-120	20.04
120-130	11.01
130-140	6.29
140-150	3.58
150-160	1.98
160-170	0.71
170-180	0.08

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 2 SEL45 UV FR 930 @700MA.IES

## COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	96
1	107	102	98	93	104	99	95	92	95	91	88	90	87	85	86	84	82	79
2	97	89	82	76	94	87	80	75	82	77	72	79	74	70	75	71	68	66
3	89	78	70	63	86	76	68	62	73	66	61	69	64	59	66	62	58	55
4	81	69	60	53	79	67	59	53	64	57	52	62	56	51	59	54	50	47
5	75	62	53	46	72	60	52	45	58	50	45	55	49	44	53	48	43	41
6	69	56	47	40	67	54	46	40	52	45	39	50	44	38	48	42	38	36
7	64	50	42	35	62	49	41	35	47	40	35	46	39	34	44	38	34	32
8	60	46	37	32	58	45	37	31	43	36	31	42	35	31	40	35	30	28
9	56	42	34	28	54	41	34	28	40	33	28	39	32	28	37	32	27	25
10	52	39	31	26	51	38	31	26	37	30	25	36	29	25	35	29	25	23

# IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 2 SEL45 UV FR 930 @700MA.IES

## UGR TABLE - CORRECTED

### Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

### Room Size UGR Viewed Crosswise


X=2H	Y=2H	21.9	23.4	22.3	23.8	24.3	24.0	25.6	24.4	26.0	26.4
	3H	23.1	24.5	23.5	24.9	25.4	26.0	27.4	26.4	27.8	28.3
	4H	23.4	24.8	23.9	25.2	25.7	26.9	28.2	27.3	28.6	29.1
	6H	23.6	24.9	24.1	25.3	25.8	27.7	28.9	28.2	29.4	29.9
	8H	23.7	24.9	24.2	25.3	25.8	28.1	29.2	28.6	29.7	30.2
	12H	23.7	24.8	24.2	25.3	25.8	28.5	29.6	29.0	30.1	30.6

### UGR Viewed Endwise

4H	2H	22.7	24.1	23.2	24.5	25.0	24.4	25.8	24.9	26.2	26.7
	3H	24.2	25.3	24.7	25.8	26.3	26.6	27.8	27.1	28.2	28.7
	4H	24.7	25.7	25.2	26.2	26.7	27.7	28.7	28.1	29.2	29.7
	6H	25.0	25.9	25.5	26.4	26.9	28.6	29.5	29.2	30.0	30.6
	8H	25.0	25.9	25.6	26.4	26.9	29.1	29.9	29.6	30.5	31.0
	12H	25.1	25.8	25.6	26.4	26.9	29.6	30.4	30.1	30.9	31.5
8H	4H	25.2	26.1	25.7	26.6	27.1	27.8	28.7	28.4	29.2	29.7
	6H	25.7	26.4	26.2	26.9	27.5	29.0	29.7	29.5	30.2	30.8
	8H	25.8	26.5	26.4	27.0	27.6	29.5	30.2	30.1	30.8	31.3
	12H	25.9	26.5	26.5	27.0	27.7	30.2	30.8	30.8	31.3	32.0
12H	4H	25.3	26.1	25.9	26.6	27.2	27.8	28.6	28.4	29.1	29.7
	6H	25.9	26.5	26.5	27.1	27.7	29.0	29.6	29.6	30.2	30.8
	8H	26.1	26.7	26.7	27.2	27.9	29.7	30.2	30.2	30.8	31.4

Maximum UGR = 32.0

POLAR GRAPH



Maximum Candela = 1515.249 Located At Horizontal Angle = 90, Vertical Angle = .5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)