

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 2 SEL25 UV FR 930 @400MA.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-003(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/6/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL N G2 2 SEL25 UV FR 930

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] One LS3872A 48 LED board, 3000K

[BALLAST] One KTLD-25-UV-PS450-54-VDIM-LP2 LED driver set at 400mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2935
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	142
Total Luminaire Watts	20.6
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	1.99 ft
Luminous Width (90-270)	0.21 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	21188	19360	19110
55	18145	16958	16929
65	14384	14165	14359
75	10326	11358	11480
85	5705	9211	9047

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 2 SEL25 UV FR 930 @400MA.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	358.88	N.A.	12.20
0-30	763.53	N.A.	26.00
0-40	1249.61	N.A.	42.60
0-60	2184.06	N.A.	74.40
0-80	2723.02	N.A.	92.80
0-90	2831.73	N.A.	96.50
10-90	2739.09	N.A.	93.30
20-40	890.73	N.A.	30.30
20-50	1387.47	N.A.	47.30
40-70	1264.51	N.A.	43.10
60-80	538.96	N.A.	18.40
70-80	208.90	N.A.	7.10
80-90	108.71	N.A.	3.70
90-110	75.18	N.A.	2.60
90-120	88.17	N.A.	3.00
90-130	95.30	N.A.	3.20
90-150	101.70	N.A.	3.50
90-180	103.49	N.A.	3.50
110-180	28.31	N.A.	1.00
0-180	2935.22	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	92.65
10-20	266.23
20-30	404.65
30-40	486.08
40-50	496.73
50-60	437.72
60-70	330.06
70-80	208.90
80-90	108.71
90-100	50.51
100-110	24.67
110-120	12.99
120-130	7.13
130-140	4.07
140-150	2.32
150-160	1.28
160-170	0.46
170-180	0.05

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 2 SEL25 UV FR 930 @400MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	96
1	107	102	98	93	104	99	95	92	95	91	88	90	87	85	86	84	82	79
2	97	89	82	76	94	87	80	75	82	77	72	79	74	70	75	71	68	66
3	89	78	70	63	86	76	68	62	73	66	61	69	64	59	66	62	58	55
4	81	69	60	53	79	67	59	53	65	57	52	62	56	51	59	54	50	47
5	75	62	53	46	72	60	52	45	58	50	45	55	49	44	53	48	43	41
6	69	56	47	40	67	54	46	40	52	45	39	50	44	38	48	42	38	36
7	64	50	42	35	62	49	41	35	47	40	35	46	39	34	44	38	34	32
8	60	46	37	32	58	45	37	31	43	36	31	42	35	31	41	35	30	28
9	56	42	34	28	54	41	34	28	40	33	28	39	32	28	37	32	27	25
10	52	39	31	26	51	38	31	26	37	30	25	36	29	25	35	29	25	23

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 2 SEL25 UV FR 930 @400MA.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise

X=2H	Y=2H	20.3	21.8	20.7	22.2	22.7	22.4	24.0	22.8	24.4	24.8
	3H	21.5	22.9	21.9	23.3	23.8	24.4	25.8	24.9	26.2	26.7
	4H	21.8	23.2	22.3	23.6	24.1	25.3	26.6	25.7	27.0	27.5
	6H	22.0	23.3	22.5	23.7	24.2	26.1	27.3	26.6	27.8	28.3
	8H	22.1	23.3	22.6	23.7	24.2	26.5	27.6	27.0	28.1	28.6
	12H	22.1	23.2	22.6	23.7	24.2	26.9	28.0	27.4	28.5	29.0

UGR Viewed Endwise


4H	2H	21.1	22.5	21.6	22.9	23.4	22.8	24.2	23.3	24.6	25.1
	3H	22.6	23.7	23.1	24.2	24.7	25.0	26.2	25.5	26.6	27.1
	4H	23.1	24.1	23.6	24.6	25.1	26.1	27.1	26.5	27.6	28.1
	6H	23.4	24.3	23.9	24.8	25.3	27.0	27.9	27.6	28.4	29.0
	8H	23.4	24.3	24.0	24.8	25.3	27.5	28.3	28.0	28.9	29.4
	12H	23.5	24.2	24.0	24.8	25.3	28.0	28.8	28.5	29.3	29.9

8H	4H	23.6	24.5	24.1	25.0	25.5	26.2	27.1	26.8	27.6	28.2
	6H	24.1	24.8	24.6	25.3	25.9	27.4	28.1	27.9	28.6	29.2
	8H	24.2	24.9	24.8	25.4	26.0	27.9	28.6	28.5	29.2	29.7
	12H	24.3	24.9	24.9	25.4	26.1	28.6	29.2	29.2	29.7	30.4

12H	4H	23.7	24.5	24.3	25.0	25.6	26.2	27.0	26.8	27.5	28.1
	6H	24.3	24.9	24.9	25.5	26.1	27.4	28.0	28.0	28.6	29.2
	8H	24.5	25.1	25.1	25.6	26.3	28.1	28.6	28.6	29.2	29.8

Maximum UGR = 30.4

POLAR GRAPH



Maximum Candela = 981.896 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)