



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 4 SEL25 UV FR 940 @350MA.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-006(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/6/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL N G2 4 SEL25 UV FR 940

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Two LS3872A 48 LED boards, 4000K

[BALLAST] One KTLD-25-UV-PS450-54-VDIM-LP2 LED driver set at 350mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2685
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	155
Total Luminaire Watts	17.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	3.84 ft
Luminous Width (90-270)	0.21 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	10407	9291	9050
55	9035	8197	8015
65	7237	6871	6725
75	5252	5480	5269
85	3023	4422	3995

IES INDOOR REPORT**PHOTOMETRIC FILENAME : ECL N G2 4 SEL25 UV FR 940 @350MA.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	329.12	N.A.	12.30
0-30	699.84	N.A.	26.10
0-40	1145.81	N.A.	42.70
0-60	2008.21	N.A.	74.80
0-80	2502.01	N.A.	93.20
0-90	2598.26	N.A.	96.80
10-90	2513.25	N.A.	93.60
20-40	816.68	N.A.	30.40
20-50	1274.38	N.A.	47.50
40-70	1166.56	N.A.	43.50
60-80	493.80	N.A.	18.40
70-80	189.64	N.A.	7.10
80-90	96.25	N.A.	3.60
90-110	64.66	N.A.	2.40
90-120	75.48	N.A.	2.80
90-130	81.20	N.A.	3.00
90-150	85.49	N.A.	3.20
90-180	86.24	N.A.	3.20
110-180	21.58	N.A.	0.80
0-180	2684.51	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	85.02
10-20	244.11
20-30	370.71
30-40	445.97
40-50	457.70
50-60	404.70
60-70	304.16
70-80	189.64
80-90	96.25
90-100	43.64
100-110	21.02
110-120	10.82
120-130	5.72
130-140	2.93
140-150	1.36
150-160	0.58
160-170	0.17
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 4 SEL25 UV FR 940 @350MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	97
1	107	102	98	94	104	100	96	92	95	91	88	90	88	85	86	84	82	80
2	97	89	82	76	94	87	80	75	83	77	73	79	74	70	75	72	68	66
3	89	78	70	63	86	76	69	62	73	66	61	70	64	59	67	62	58	56
4	81	69	60	53	79	68	59	53	65	57	52	62	56	51	59	54	50	47
5	75	62	53	46	72	60	52	46	58	50	45	56	49	44	53	48	43	41
6	69	56	47	40	67	54	46	40	52	45	39	50	44	39	48	43	38	36
7	64	50	42	35	62	49	41	35	48	40	35	46	39	34	44	38	34	32
8	60	46	37	32	58	45	37	31	44	36	31	42	35	31	41	35	30	28
9	56	42	34	28	54	41	34	28	40	33	28	39	32	28	38	32	27	25
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 4 SEL25 UV FR 940 @350MA.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise

X=2H	Y=2H	17.9	19.5	18.3	19.9	20.3	19.9	21.5	20.3	21.9	22.3
	3H	19.1	20.6	19.6	20.9	21.4	21.9	23.3	22.3	23.7	24.2
	4H	19.5	20.8	19.9	21.2	21.7	22.8	24.1	23.2	24.5	25.0
	6H	19.7	20.9	20.1	21.4	21.8	23.5	24.8	24.0	25.2	25.7
	8H	19.7	20.9	20.2	21.4	21.8	23.9	25.1	24.4	25.6	26.0
	12H	19.7	20.9	20.2	21.3	21.8	24.3	25.5	24.8	25.9	26.4

UGR Viewed Endwise


4H	2H	18.8	20.1	19.2	20.5	21.0	20.4	21.7	20.8	22.1	22.6
	3H	20.2	21.3	20.6	21.8	22.3	22.5	23.7	23.0	24.1	24.6
	4H	20.7	21.7	21.1	22.2	22.7	23.5	24.6	24.0	25.0	25.5
	6H	21.0	21.9	21.5	22.4	22.9	24.5	25.4	25.0	25.9	26.4
	8H	21.0	21.9	21.5	22.4	22.9	24.9	25.8	25.4	26.3	26.8
	12H	21.1	21.8	21.6	22.4	22.9	25.4	26.2	25.9	26.7	27.3

8H	4H	21.2	22.1	21.7	22.6	23.1	23.7	24.6	24.2	25.1	25.6
	6H	21.7	22.4	22.2	22.9	23.5	24.8	25.5	25.3	26.1	26.6
	8H	21.8	22.5	22.3	23.0	23.6	25.4	26.0	25.9	26.6	27.1
	12H	21.9	22.5	22.4	23.0	23.6	26.0	26.6	26.5	27.1	27.7

12H	4H	21.3	22.1	21.8	22.6	23.2	23.7	24.5	24.2	25.0	25.6
	6H	21.9	22.5	22.4	23.0	23.6	24.8	25.5	25.4	26.0	26.6
	8H	22.1	22.7	22.6	23.2	23.8	25.5	26.0	26.0	26.6	27.2

Maximum UGR = 27.7

POLAR GRAPH



Maximum Candela = 902.863 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)