



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 6 SEL15 UV FR 935 @270MA.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-006(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/6/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL N G2 6 SEL15 UV FR 935

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Three LS3872A 28 LED boards, 3500K

[BALLAST] One KTLD-15-UV-PS300-54-VDIM-LP1 LED driver set at 270mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1766
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	146
Total Luminaire Watts	12.1
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	5.84 ft
Luminous Width (90-270)	0.21 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	4528	4033	3916
55	3940	3562	3468
65	3168	2990	2910
75	2318	2390	2280
85	1382	1938	1728

IES INDOOR REPORT**PHOTOMETRIC FILENAME : ECL N G2 6 SEL15 UV FR 935 @270MA.IES****ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	216.49	N.A.	12.30
0-30	460.33	N.A.	26.10
0-40	753.68	N.A.	42.70
0-60	1320.94	N.A.	74.80
0-80	1645.74	N.A.	93.20
0-90	1709.05	N.A.	96.80
10-90	1653.13	N.A.	93.60
20-40	537.19	N.A.	30.40
20-50	838.25	N.A.	47.50
40-70	767.33	N.A.	43.50
60-80	324.81	N.A.	18.40
70-80	124.74	N.A.	7.10
80-90	63.31	N.A.	3.60
90-110	42.53	N.A.	2.40
90-120	49.65	N.A.	2.80
90-130	53.41	N.A.	3.00
90-150	56.23	N.A.	3.20
90-180	56.73	N.A.	3.20
110-180	14.20	N.A.	0.80
0-180	1765.78	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	55.92
10-20	160.57
20-30	243.84
30-40	293.34
40-50	301.06
50-60	266.20
60-70	200.07
70-80	124.74
80-90	63.31
90-100	28.71
100-110	13.82
110-120	7.12
120-130	3.76
130-140	1.93
140-150	0.90
150-160	0.38
160-170	0.11
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 6 SEL15 UV FR 935 @270MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	97
1	107	102	98	94	104	100	96	92	95	91	88	90	88	85	86	84	82	80
2	97	89	82	76	94	87	80	75	83	77	73	79	74	70	75	72	68	66
3	89	78	70	63	86	76	69	62	73	66	61	70	64	59	67	62	58	56
4	81	69	60	53	79	68	59	53	65	57	52	62	56	51	59	54	50	47
5	75	62	53	46	72	60	52	46	58	50	45	56	49	44	53	48	43	41
6	69	56	47	40	67	54	46	40	52	45	39	50	44	39	48	43	38	36
7	64	50	42	35	62	49	41	35	48	40	35	46	39	34	44	38	34	32
8	60	46	37	32	58	45	37	31	44	36	31	42	35	31	41	35	30	28
9	56	42	34	28	54	41	34	28	40	33	28	39	32	28	38	32	27	25
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 6 SEL15 UV FR 935 @270MA.IES

UGR TABLE - CORRECTED

Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size UGR Viewed Crosswise

X=2H	Y=2H	15.1	16.6	15.5	17.0	17.4	17.1	18.7	17.5	19.1	19.5
	3H	16.3	17.7	16.7	18.1	18.5	19.1	20.5	19.5	20.9	21.3
	4H	16.6	18.0	17.1	18.4	18.8	19.9	21.3	20.4	21.7	22.1
	6H	16.8	18.1	17.3	18.5	19.0	20.7	22.0	21.2	22.4	22.9
	8H	16.8	18.1	17.3	18.5	19.0	21.1	22.3	21.6	22.8	23.2
	12H	16.9	18.0	17.3	18.5	19.0	21.5	22.7	22.0	23.1	23.6

UGR Viewed Endwise


4H	2H	15.9	17.3	16.4	17.7	18.1	17.5	18.9	18.0	19.3	19.7
	3H	17.3	18.5	17.8	18.9	19.4	19.7	20.9	20.2	21.3	21.8
	4H	17.8	18.9	18.3	19.3	19.8	20.7	21.7	21.2	22.2	22.7
	6H	18.1	19.0	18.6	19.5	20.1	21.7	22.6	22.2	23.1	23.6
	8H	18.2	19.0	18.7	19.5	20.1	22.1	23.0	22.6	23.5	24.0
	12H	18.2	19.0	18.7	19.5	20.1	22.6	23.4	23.1	23.9	24.5

8H	4H	18.4	19.2	18.9	19.7	20.3	20.9	21.8	21.4	22.2	22.8
	6H	18.8	19.5	19.4	20.1	20.6	22.0	22.7	22.5	23.3	23.8
	8H	19.0	19.6	19.5	20.2	20.7	22.6	23.2	23.1	23.8	24.3
	12H	19.1	19.6	19.6	20.2	20.8	23.2	23.8	23.8	24.3	25.0

12H	4H	18.5	19.3	19.0	19.8	20.3	20.9	21.7	21.4	22.2	22.7
	6H	19.0	19.7	19.6	20.2	20.8	22.0	22.7	22.6	23.2	23.8
	8H	19.2	19.8	19.8	20.4	21.0	22.7	23.2	23.2	23.8	24.4

Maximum UGR = 25.0

POLAR GRAPH



Maximum Candela = 593.875 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)