



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 6 SEL25 UV FR 930 @400MA.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001735-006(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/6/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL N G2 6 SEL25 UV FR 930

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Three LS3872A 28 LED boards, 3000K

[BALLAST] One KTLD-25-UV-PS450-54-VDIM-LP2 LED driver set at 400mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2614
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	150
Total Luminaire Watts	17.4
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	5.84 ft
Luminous Width (90-270)	0.21 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	6703	5971	5797
55	5833	5274	5134
65	4691	4427	4308
75	3432	3539	3376
85	2047	2869	2559

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 6 SEL25 UV FR 930 @400MA.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	320.52	N.A.	12.30
0-30	681.55	N.A.	26.10
0-40	1115.86	N.A.	42.70
0-60	1955.73	N.A.	74.80
0-80	2436.63	N.A.	93.20
0-90	2530.37	N.A.	96.80
10-90	2447.57	N.A.	93.60
20-40	795.34	N.A.	30.40
20-50	1241.08	N.A.	47.50
40-70	1136.08	N.A.	43.50
60-80	480.90	N.A.	18.40
70-80	184.69	N.A.	7.10
80-90	93.73	N.A.	3.60
90-110	62.97	N.A.	2.40
90-120	73.50	N.A.	2.80
90-130	79.08	N.A.	3.00
90-150	83.26	N.A.	3.20
90-180	83.99	N.A.	3.20
110-180	21.02	N.A.	0.80
0-180	2614.36	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	82.79
10-20	237.73
20-30	361.03
30-40	434.32
40-50	445.74
50-60	394.13
60-70	296.21
70-80	184.69
80-90	93.73
90-100	42.50
100-110	20.47
110-120	10.54
120-130	5.57
130-140	2.85
140-150	1.33
150-160	0.57
160-170	0.16
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 6 SEL25 UV FR 930 @400MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	97
1	107	102	98	94	104	100	96	92	95	91	88	90	88	85	86	84	82	80
2	97	89	82	76	95	87	80	75	83	77	73	79	74	70	75	72	68	66
3	89	78	70	63	86	76	69	62	73	66	61	70	64	59	67	62	58	56
4	81	69	60	53	79	68	59	53	65	57	52	62	56	51	59	54	50	47
5	75	62	53	46	72	60	52	46	58	50	45	56	49	44	53	48	43	41
6	69	56	47	40	67	54	46	40	52	45	39	50	44	39	48	43	38	36
7	64	50	42	35	62	49	41	35	48	40	35	46	39	34	44	38	34	32
8	60	46	37	32	58	45	37	31	44	36	31	42	35	31	41	35	30	28
9	56	42	34	28	54	41	34	28	40	33	28	39	32	28	38	32	27	25
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23


IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 6 SEL25 UV FR 930 @400MA.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size											
		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	16.4	17.9	16.8	18.3	18.7	18.4	20.0	18.8	20.4	20.8
	3H	17.6	19.0	18.0	19.4	19.8	20.4	21.8	20.8	22.2	22.6
	4H	17.9	19.3	18.4	19.7	20.1	21.2	22.6	21.7	23.0	23.4
	6H	18.1	19.4	18.6	19.8	20.3	22.0	23.3	22.5	23.7	24.2
	8H	18.1	19.4	18.6	19.8	20.3	22.4	23.6	22.9	24.1	24.5
	12H	18.2	19.3	18.6	19.8	20.3	22.8	24.0	23.3	24.4	24.9
4H	2H	17.2	18.6	17.7	19.0	19.4	18.8	20.2	19.3	20.6	21.0
	3H	18.6	19.8	19.1	20.2	20.7	21.0	22.2	21.5	22.6	23.1
	4H	19.1	20.2	19.6	20.6	21.1	22.0	23.0	22.5	23.5	24.0
	6H	19.4	20.3	19.9	20.8	21.4	23.0	23.9	23.5	24.4	24.9
	8H	19.5	20.3	20.0	20.8	21.4	23.4	24.3	23.9	24.8	25.3
	12H	19.5	20.3	20.0	20.8	21.4	23.9	24.7	24.4	25.2	25.8
8H	4H	19.7	20.5	20.2	21.0	21.6	22.2	23.1	22.7	23.5	24.1
	6H	20.1	20.8	20.7	21.4	21.9	23.3	24.0	23.8	24.6	25.1
	8H	20.2	20.9	20.8	21.5	22.0	23.9	24.5	24.4	25.1	25.6
	12H	20.4	20.9	20.9	21.5	22.1	24.5	25.1	25.1	25.6	26.3
12H	4H	19.8	20.6	20.3	21.1	21.6	22.2	23.0	22.7	23.5	24.0
	6H	20.3	21.0	20.9	21.5	22.1	23.3	24.0	23.9	24.5	25.1
	8H	20.5	21.1	21.1	21.7	22.3	24.0	24.5	24.5	25.1	25.7

Maximum UGR = 26.3

POLAR GRAPH



Maximum Candela = 879.27 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)