



IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 6 SEL45 UV FR 940 @700MA.IES

DESCRIPTION INFORMATION (From Photometric File)

[IESNA] LM-63-2002

[TEST] LLIA001735-006(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/6/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] ECL N G2 6 SEL45 UV FR 940

[LUMINAIRE] Surface or suspended mounted, formed white painted steel housing/reflector,

[MORE] translucent curved plastic enclosure.

[LAMPCAT] Three LS3872A 48 LED boards, 4000K

[BALLAST] One KTLD-45-UV-PS850-54-VDIM-LM1 LED driver set at 700mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5376
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	157
Total Luminaire Watts	34.2
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.24
Spacing Criterion (90-270)	1.30
Spacing Criterion (Diagonal)	1.38
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	5.84 ft
Luminous Width (90-270)	0.21 ft
Luminous Height	0.06 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	13783	12277	11921
55	11995	10844	10557
65	9645	9102	8858
75	7056	7277	6941
85	4209	5899	5262

IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 6 SEL45 UV FR 940 @700MA.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	659.06	N.A.	12.30
0-30	1401.41	N.A.	26.10
0-40	2294.45	N.A.	42.70
0-60	4021.39	N.A.	74.80
0-80	5010.22	N.A.	93.20
0-90	5202.96	N.A.	96.80
10-90	5032.72	N.A.	93.60
20-40	1635.39	N.A.	30.40
20-50	2551.92	N.A.	47.50
40-70	2336.01	N.A.	43.50
60-80	988.83	N.A.	18.40
70-80	379.76	N.A.	7.10
80-90	192.74	N.A.	3.60
90-110	129.48	N.A.	2.40
90-120	151.14	N.A.	2.80
90-130	162.60	N.A.	3.00
90-150	171.19	N.A.	3.20
90-180	172.70	N.A.	3.20
110-180	43.22	N.A.	0.80
0-180	5375.66	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	170.24
10-20	488.82
20-30	742.35
30-40	893.04
40-50	916.53
50-60	810.41
60-70	609.08
70-80	379.76
80-90	192.74
90-100	87.39
100-110	42.09
110-120	21.66
120-130	11.46
130-140	5.86
140-150	2.73
150-160	1.17
160-170	0.34
170-180	0.00

IES INDOOR REPORT

PHOTOMETRIC FILENAME : ECL N G2 6 SEL45 UV FR 940 @700MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	97
1	107	102	98	94	104	100	96	92	95	91	88	90	88	85	86	84	82	80
2	97	89	82	76	94	87	80	75	83	77	73	79	74	70	75	72	68	66
3	89	78	70	63	86	76	69	62	73	66	61	70	64	59	67	62	58	56
4	81	69	60	53	79	68	59	53	65	57	52	62	56	51	59	54	50	47
5	75	62	53	46	72	60	52	46	58	50	45	56	49	44	53	48	43	41
6	69	56	47	40	67	54	46	40	52	45	39	50	44	39	48	43	38	36
7	64	50	42	35	62	49	41	35	48	40	35	46	39	34	44	38	34	32
8	60	46	37	32	58	45	37	31	44	36	31	42	35	31	41	35	30	28
9	56	42	34	28	54	41	34	28	40	33	28	39	32	28	38	32	27	25
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	35	29	25	23


IES INDOOR REPORT
PHOTOMETRIC FILENAME : ECL N G2 6 SEL45 UV FR 940 @700MA.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size											
		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	18.9	20.4	19.3	20.8	21.2	20.9	22.5	21.3	22.9	23.3
	3H	20.1	21.5	20.5	21.9	22.3	22.9	24.3	23.3	24.7	25.1
	4H	20.4	21.8	20.9	22.2	22.6	23.7	25.1	24.2	25.5	25.9
	6H	20.6	21.9	21.1	22.3	22.8	24.5	25.8	25.0	26.2	26.7
	8H	20.6	21.9	21.1	22.3	22.8	24.9	26.1	25.4	26.6	27.0
	12H	20.7	21.8	21.1	22.3	22.8	25.3	26.5	25.8	26.9	27.4
4H	2H	19.7	21.1	20.2	21.5	21.9	21.3	22.7	21.8	23.1	23.5
	3H	21.1	22.3	21.6	22.7	23.2	23.5	24.7	24.0	25.1	25.6
	4H	21.6	22.7	22.1	23.1	23.6	24.5	25.5	25.0	26.0	26.5
	6H	21.9	22.8	22.4	23.3	23.9	25.5	26.4	26.0	26.9	27.4
	8H	22.0	22.8	22.5	23.3	23.9	25.9	26.8	26.4	27.3	27.8
	12H	22.0	22.8	22.5	23.3	23.9	26.4	27.2	26.9	27.7	28.3
8H	4H	22.2	23.0	22.7	23.5	24.1	24.7	25.6	25.2	26.0	26.6
	6H	22.6	23.3	23.2	23.9	24.4	25.8	26.5	26.3	27.1	27.6
	8H	22.7	23.4	23.3	24.0	24.5	26.4	27.0	26.9	27.6	28.1
	12H	22.9	23.4	23.4	24.0	24.6	27.0	27.6	27.6	28.1	28.8
12H	4H	22.3	23.1	22.8	23.6	24.1	24.7	25.5	25.2	26.0	26.5
	6H	22.8	23.5	23.4	24.0	24.6	25.8	26.5	26.4	27.0	27.6
	8H	23.0	23.6	23.6	24.2	24.8	26.5	27.0	27.0	27.6	28.2

Maximum UGR = 28.8

POLAR GRAPH



Maximum Candela = 1807.963 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)