



IES INDOOR REPORT

PHOTOMETRIC FILENAME : FFL G2 22 SEL15 UV FA 935 @200MA.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001588-024 (s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/3/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] FFL G2 22 SEL15 UV FA 935

[LUMINAIRE] Recessed mounted, formed white painted steel housing/reflector,
[MORE] frosted linear ribbed plastic enclosure.

[LAMP] One LS3872A7_3500_90R 3500K 48 LED board

[BALLAST] One KTLD-15-UV-PS300-54-VDIM-LP1 LED driver set to 200mA

[OTHER] 120.0Vac, 60.01Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1404
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	136
Total Luminaire Watts	10.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.26
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	1.85 ft
Luminous Width (90-270)	1.85 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1287	1388	1490
55	1184	1343	1511
65	1065	1321	1602
75	896	1331	1755
85	597	1133	1564

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFL G2 22 SEL15 UV FA 935 @200MA.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	179.44	N.A.	12.80
0-30	378.11	N.A.	26.90
0-40	614.06	N.A.	43.70
0-60	1077.01	N.A.	76.70
0-80	1370.13	N.A.	97.60
0-90	1404.43	N.A.	100.00
10-90	1357.76	N.A.	96.70
20-40	434.62	N.A.	30.90
20-50	676.84	N.A.	48.20
40-70	640.37	N.A.	45.60
60-80	293.11	N.A.	20.90
70-80	115.70	N.A.	8.20
80-90	34.30	N.A.	2.40
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1404.43	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	46.67
10-20	132.77
20-30	198.67
30-40	235.95
40-50	242.22
50-60	220.73
60-70	177.41
70-80	115.70
80-90	34.30
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFL G2 22 SEL15 UV FA 935 @200MA.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	106	101	97	93	97	93	90	93	90	87	89	87	85	83
2	98	90	83	77	96	88	81	76	84	79	74	81	76	72	78	74	71	68
3	89	79	70	63	87	77	69	63	74	67	62	71	65	61	69	64	60	57
4	82	69	60	54	79	68	60	53	66	58	52	63	57	52	61	56	51	49
5	75	62	53	46	73	61	52	46	59	51	45	57	50	45	55	49	44	42
6	69	56	47	40	67	55	46	40	53	45	40	51	45	39	50	44	39	37
7	64	51	42	36	63	50	41	35	48	41	35	47	40	35	45	39	35	33
8	60	46	38	32	58	46	37	32	44	37	31	43	36	31	42	36	31	29
9	56	42	34	29	55	42	34	28	41	33	28	40	33	28	39	32	28	26
10	52	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	25	24


IES INDOOR REPORT
PHOTOMETRIC FILENAME : FFL G2 22 SEL15 UV FA 935 @200MA.IES

UGR TABLE - CORRECTED

Reflectances											
Ceiling Cavity		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
Floor Cavity		20	20	20	20	20	20	20	20	20	20
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	12.4	14.0	12.7	14.3	14.7	13.8	15.5	14.2	15.8	16.1
	3H	14.1	15.6	14.5	15.9	16.3	16.2	17.7	16.6	18.0	18.4
	4H	14.7	16.2	15.1	16.5	16.9	17.2	18.7	17.6	19.0	19.4
	6H	15.2	16.5	15.6	16.9	17.2	18.1	19.5	18.6	19.8	20.2
	8H	15.3	16.6	15.7	16.9	17.3	18.5	19.8	18.9	20.2	20.5
	12H	15.4	16.6	15.8	17.0	17.4	18.7	19.9	19.2	20.3	20.7
4H	2H	13.3	14.7	13.7	15.0	15.4	14.4	15.8	14.8	16.2	16.5
	3H	15.2	16.4	15.6	16.8	17.2	17.0	18.2	17.4	18.6	19.0
	4H	16.0	17.1	16.4	17.5	17.9	18.2	19.3	18.6	19.7	20.2
	6H	16.6	17.5	17.0	17.9	18.4	19.3	20.3	19.8	20.7	21.2
	8H	16.7	17.6	17.2	18.1	18.5	19.7	20.6	20.2	21.1	21.5
	12H	16.8	17.6	17.3	18.1	18.6	20.0	20.8	20.5	21.3	21.8
8H	4H	16.6	17.5	17.0	17.9	18.4	18.5	19.4	19.0	19.8	20.3
	6H	17.3	18.1	17.8	18.5	19.0	19.8	20.5	20.3	21.0	21.5
	8H	17.5	18.2	18.0	18.7	19.2	20.3	21.0	20.8	21.5	22.0
	12H	17.7	18.3	18.2	18.8	19.4	20.7	21.3	21.2	21.8	22.3
12H	4H	16.7	17.5	17.2	18.0	18.5	18.5	19.3	19.0	19.8	20.3
	6H	17.5	18.2	18.0	18.6	19.2	19.8	20.5	20.3	21.0	21.5
	8H	17.8	18.4	18.3	18.9	19.5	20.4	21.0	20.9	21.5	22.0

Maximum UGR = 22.3

POLAR GRAPH



Maximum Candela = 494.184 Located At Horizontal Angle = 90, Vertical Angle = .5
1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)