



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : FFR G2 22 SEL15 UV FA 935 @200MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001588-014 (s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/4/2024

[MANUFAC] Lumen Focus, LLC

[LUMCAT] FFR G2 22 SEL15 UV FA 935

[LUMINAIRE] Retrofit kit installed in an A.L.P. EL-2x2-20-2 2x2 housing,

[MORE] formed white painted steel reflectors, frosted linear ribbed plastic enclosure.

[LAMPCAT] One LS3872A7\_3500\_90R 3500K 48 LED board

[BALLAST] One KTLD-15-UV-PS300-54-VDIM-LP1 LED driver set to 200mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1445
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	140
Total Luminaire Watts	10.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	1.84 ft
Luminous Width (90-270)	1.84 ft
Luminous Height	0.00 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1314	1439	1569
55	1205	1399	1610
65	1079	1383	1716
75	912	1400	1935
85	657	1181	1323

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 22 SEL15 UV FA 935 @200MA.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	183.33	N.A.	12.70
0-30	386.32	N.A.	26.70
0-40	627.66	N.A.	43.50
0-60	1104.04	N.A.	76.40
0-80	1409.59	N.A.	97.60
0-90	1444.54	N.A.	100.00
10-90	1396.85	N.A.	96.70
20-40	444.33	N.A.	30.80
20-50	692.94	N.A.	48.00
40-70	660.25	N.A.	45.70
60-80	305.55	N.A.	21.20
70-80	121.68	N.A.	8.40
80-90	34.95	N.A.	2.40
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1444.54	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	47.69
10-20	135.64
20-30	202.98
30-40	241.35
40-50	248.61
50-60	227.78
60-70	183.87
70-80	121.68
80-90	34.95
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 22 SEL15 UV FA 935 @200MA.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	105	101	97	93	97	93	90	93	90	87	89	87	85	83
2	98	89	82	76	95	88	81	76	84	78	74	81	76	72	78	74	70	68
3	89	78	70	63	87	77	69	63	74	67	62	71	65	60	68	64	59	57
4	82	69	60	53	79	68	60	53	65	58	52	63	57	52	61	55	51	49
5	75	62	53	46	73	61	52	46	59	51	45	57	50	45	55	49	44	42
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	50	43	39	37
7	64	50	42	35	62	50	41	35	48	40	35	47	40	35	45	39	34	32
8	60	46	37	32	58	45	37	31	44	37	31	43	36	31	42	35	31	29
9	56	42	34	28	54	42	34	28	41	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	26	37	30	25	36	30	25	24

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 22 SEL15 UV FA 935 @200MA.IES**

**UGR TABLE - CORRECTED**


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	12.4	14.1	12.8	14.4	14.7	14.1	15.8	14.5	16.1	16.4
	3H	14.1	15.6	14.5	16.0	16.3	16.5	18.0	16.9	18.4	18.7
	4H	14.7	16.2	15.1	16.5	16.9	17.6	19.0	18.0	19.4	19.7
	6H	15.2	16.5	15.6	16.9	17.3	18.5	19.9	19.0	20.2	20.6
	8H	15.3	16.6	15.8	17.0	17.4	18.9	20.1	19.3	20.5	20.9
	12H	15.4	16.6	15.9	17.0	17.4	19.0	20.2	19.4	20.6	21.0
4H	2H	13.3	14.7	13.7	15.1	15.5	14.6	16.1	15.0	16.4	16.8
	3H	15.3	16.5	15.7	16.9	17.3	17.3	18.5	17.7	18.9	19.3
	4H	16.0	17.1	16.5	17.5	18.0	18.6	19.7	19.0	20.1	20.5
	6H	16.6	17.6	17.0	18.0	18.5	19.7	20.7	20.1	21.1	21.6
	8H	16.8	17.7	17.3	18.1	18.6	20.1	21.0	20.5	21.4	21.9
	12H	16.9	17.7	17.4	18.2	18.7	20.3	21.1	20.8	21.6	22.0
8H	4H	16.7	17.6	17.1	18.0	18.5	18.8	19.7	19.3	20.2	20.6
	6H	17.4	18.2	17.9	18.7	19.1	20.2	20.9	20.6	21.4	21.9
	8H	17.7	18.4	18.2	18.9	19.3	20.6	21.3	21.1	21.8	22.3
	12H	17.9	18.5	18.4	19.0	19.5	20.9	21.5	21.4	22.0	22.6
12H	4H	16.8	17.6	17.3	18.1	18.6	18.9	19.7	19.3	20.2	20.6
	6H	17.6	18.3	18.2	18.8	19.3	20.2	20.9	20.7	21.3	21.9
	8H	18.0	18.6	18.5	19.1	19.6	20.7	21.3	21.2	21.8	22.4

Maximum UGR = 22.6

POLAR GRAPH



Maximum Candela = 505.652 Located At Horizontal Angle = 90, Vertical Angle = .5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (.5) (Through Max. Cd.)