



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 930 @350MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001588-007A (s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/4/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] FFR G2 24 SEL25 UV FA 930

[LUMINAIRE] Retrofit kit installed in an A.L.P. EL-2x4-23-2 2x4 housing,

[MORE] formed white painted steel reflectors, frosted linear ribbed plastic enclosure.

[LAMP] Two LS3873A7\_3000\_90R 3000K 48 LED boards

[BALLAST] One KTLD-25-UV-PS450-54-VDIM-LP2 LED driver set to 350mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2555
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	148
Total Luminaire Watts	17.3
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	3.75 ft
Luminous Width (90-270)	1.75 ft
Luminous Height	0.00 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1213	1320	1425
55	1114	1288	1461
65	998	1279	1550
75	838	1312	1733
85	565	1152	1195

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 930 @350MA.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	321.94	N.A.	12.60
0-30	679.48	N.A.	26.60
0-40	1105.63	N.A.	43.30
0-60	1949.02	N.A.	76.30
0-80	2491.61	N.A.	97.50
0-90	2554.8	N.A.	100.00
10-90	2471.15	N.A.	96.70
20-40	783.69	N.A.	30.70
20-50	1223.51	N.A.	47.90
40-70	1169.64	N.A.	45.80
60-80	542.59	N.A.	21.20
70-80	216.34	N.A.	8.50
80-90	63.19	N.A.	2.50
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	2554.8	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	83.65
10-20	238.30
20-30	357.54
30-40	426.15
40-50	439.82
50-60	403.57
60-70	326.25
70-80	216.34
80-90	63.19
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 930 @350MA.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	105	101	97	93	97	93	90	93	90	87	89	87	85	83
2	98	89	82	76	95	88	81	75	84	78	74	81	76	72	78	74	70	68
3	89	78	70	63	87	77	69	63	74	67	61	71	65	60	68	63	59	57
4	82	69	60	53	79	68	59	53	65	58	52	63	57	51	61	55	51	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	45	55	49	44	42
6	69	56	46	40	67	55	46	40	53	45	39	51	44	39	49	43	39	37
7	64	50	41	35	62	50	41	35	48	40	35	47	40	35	45	39	34	32
8	60	46	37	31	58	45	37	31	44	36	31	43	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	36	30	25	23

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 930 @350MA.IES**

**UGR TABLE - CORRECTED**


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	12.2	13.8	12.5	14.2	14.5	13.8	15.5	14.2	15.8	16.1
	3H	13.9	15.4	14.3	15.7	16.1	16.2	17.7	16.6	18.0	18.4
	4H	14.5	16.0	14.9	16.3	16.7	17.2	18.7	17.6	19.0	19.4
	6H	15.0	16.3	15.4	16.7	17.1	18.2	19.5	18.6	19.9	20.2
	8H	15.1	16.4	15.5	16.8	17.2	18.5	19.7	18.9	20.1	20.5
	12H	15.2	16.4	15.6	16.8	17.2	18.6	19.8	19.0	20.2	20.6
4H	2H	13.1	14.5	13.5	14.9	15.3	14.4	15.8	14.8	16.1	16.5
	3H	15.1	16.3	15.5	16.7	17.1	17.0	18.2	17.4	18.6	19.0
	4H	15.8	16.9	16.3	17.3	17.8	18.2	19.3	18.7	19.7	20.2
	6H	16.4	17.4	16.9	17.8	18.3	19.3	20.3	19.8	20.7	21.2
	8H	16.6	17.5	17.1	17.9	18.4	19.7	20.6	20.2	21.0	21.5
	12H	16.7	17.5	17.2	18.0	18.5	19.9	20.7	20.4	21.2	21.7
8H	4H	16.5	17.4	17.0	17.8	18.3	18.5	19.4	19.0	19.9	20.3
	6H	17.3	18.0	17.7	18.5	19.0	19.8	20.6	20.3	21.1	21.5
	8H	17.5	18.2	18.0	18.7	19.2	20.3	20.9	20.8	21.5	21.9
	12H	17.7	18.3	18.2	18.8	19.4	20.6	21.2	21.1	21.7	22.2
12H	4H	16.6	17.4	17.1	17.9	18.4	18.6	19.4	19.0	19.9	20.3
	6H	17.5	18.2	18.0	18.6	19.1	19.9	20.6	20.4	21.0	21.6
	8H	17.8	18.4	18.3	18.9	19.5	20.4	21.0	20.9	21.5	22.0

Maximum UGR = 22.2

POLAR GRAPH



Maximum Candela = 886.154 Located At Horizontal Angle = 90, Vertical Angle = 1.5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (1.5) (Through Max. Cd.)