



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 940 @300MA.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA001588-007A (s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 6/4/2024

[MANUFAC] LumenFocus, LLC

[LUMCAT] FFR G2 24 SEL25 UV FA 940

[LUMINAIRE] Retrofit kit installed in an A.L.P. EL-2x4-23-2 2x4 housing,

[MORE] formed white painted steel reflectors, frosted linear ribbed plastic enclosure.

[LAMP] Two LS3873A7\_4000\_90R 4000K 48 LED boards

[BALLAST] One KTLD-25-UV-PS450-54-VDIM-LP2 LED driver set to 300mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2248
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	152
Total Luminaire Watts	14.8
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	3.75 ft
Luminous Width (90-270)	1.75 ft
Luminous Height	0.00 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	1067	1162	1254
55	980	1133	1285
65	878	1125	1363
75	737	1155	1525
85	497	1014	1051

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 940 @300MA.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	283.24	N.A.	12.60
0-30	597.79	N.A.	26.60
0-40	972.71	N.A.	43.30
0-60	1714.71	N.A.	76.30
0-80	2192.07	N.A.	97.50
0-90	2247.66	N.A.	100.00
10-90	2174.07	N.A.	96.70
20-40	689.48	N.A.	30.70
20-50	1076.42	N.A.	47.90
40-70	1029.02	N.A.	45.80
60-80	477.36	N.A.	21.20
70-80	190.33	N.A.	8.50
80-90	55.59	N.A.	2.50
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	2247.66	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	73.59
10-20	209.65
20-30	314.56
30-40	374.92
40-50	386.94
50-60	355.05
60-70	287.03
70-80	190.33
80-90	55.59
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 940 @300MA.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	108	103	99	95	105	101	97	93	97	93	90	93	90	87	89	87	85	83
2	98	89	82	76	95	88	81	75	84	78	74	81	76	72	78	74	70	68
3	89	78	70	63	87	77	69	63	74	67	61	71	65	60	68	63	59	57
4	82	69	60	53	79	68	59	53	65	58	52	63	57	51	61	55	51	48
5	75	62	53	46	73	61	52	46	58	51	45	56	50	44	55	49	44	42
6	69	56	46	40	67	55	46	40	53	45	39	51	44	39	49	43	39	37
7	64	50	41	35	62	50	41	35	48	40	35	47	40	35	45	39	34	32
8	60	46	37	31	58	45	37	31	44	36	31	43	36	31	41	35	31	29
9	56	42	34	28	54	42	34	28	40	33	28	39	33	28	38	32	28	26
10	52	39	31	26	51	38	31	26	37	30	25	36	30	25	36	30	25	23

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : FFR G2 24 SEL25 UV FA 940 @300MA.IES**

**UGR TABLE - CORRECTED**


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	11.7	13.3	12.0	13.6	14.0	13.3	15.0	13.7	15.3	15.6
	3H	13.4	14.9	13.8	15.2	15.6	15.7	17.2	16.1	17.5	17.9
	4H	14.0	15.5	14.4	15.8	16.2	16.7	18.2	17.1	18.5	18.9
	6H	14.5	15.8	14.9	16.2	16.6	17.7	19.0	18.1	19.4	19.7
	8H	14.6	15.9	15.0	16.3	16.7	18.0	19.2	18.4	19.6	20.0
	12H	14.7	15.9	15.1	16.3	16.7	18.1	19.3	18.5	19.7	20.1
4H	2H	12.6	14.0	13.0	14.4	14.7	13.9	15.3	14.2	15.6	16.0
	3H	14.6	15.8	15.0	16.2	16.6	16.5	17.7	16.9	18.1	18.5
	4H	15.3	16.4	15.8	16.8	17.3	17.7	18.8	18.2	19.2	19.7
	6H	15.9	16.9	16.3	17.3	17.8	18.8	19.8	19.3	20.2	20.7
	8H	16.1	17.0	16.6	17.4	17.9	19.2	20.1	19.7	20.5	21.0
	12H	16.2	17.0	16.7	17.5	18.0	19.4	20.2	19.9	20.7	21.2
8H	4H	16.0	16.9	16.5	17.3	17.8	18.0	18.9	18.5	19.4	19.8
	6H	16.8	17.5	17.2	18.0	18.5	19.3	20.1	19.8	20.6	21.0
	8H	17.0	17.7	17.5	18.2	18.7	19.8	20.4	20.3	21.0	21.4
	12H	17.2	17.8	17.7	18.3	18.9	20.1	20.7	20.6	21.2	21.7
12H	4H	16.1	16.9	16.6	17.4	17.9	18.1	18.9	18.5	19.4	19.8
	6H	17.0	17.7	17.5	18.1	18.6	19.4	20.1	19.9	20.5	21.1
	8H	17.3	17.9	17.8	18.4	19.0	19.9	20.5	20.4	21.0	21.5

Maximum UGR = 21.7

POLAR GRAPH



Maximum Candela = 779.62 Located At Horizontal Angle = 90, Vertical Angle = 1.5  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (1.5) (Through Max. Cd.)