

Project: _____
 Location: _____
 Cat. #: _____
 Type: _____
 Quantity: _____




FPB v2 Select | LED Selectable Backlit Flat Panel

Features:

- High performance LED technology
- **All models sold in 2 packs only**
- Field selectable color temperature: 3000K / 3500K / 4000K / 5000K / 6500K for non-EM models; 3500K / 4000K / 5000K for EM models
- Field selectable output: choose from five wattage outputs for non-EM models; three wattage outputs for EM models
- 0-10V dimming standard (10%-100%)
- Uniform illumination with no visible LED pixilation
- Recessed in grid ceilings with integral clips for secure attachment. Surface mount and suspension cable mount kits available

CCT Selectable



Wattage Selectable

Applications:

Suitable for most commercial and institutional applications

- Office
- Retail
- Classrooms
- Healthcare Facilities

Construction:

- Steel die-formed back enclosure and frame in white finish
- PMMA lensing over LEDs - will not discolor over time

Certifications:

- UL listed for damp locations
- IC-rated for insulated ceilings
- RoHS, FCC



Lifetime:

- 50,000 hrs rated life
- L70: >60,000 hrs (reported)
88.6% lumen maintenance @ 60,000hrs
- L90: 52,000 hrs
(based on LM-80, TM-21 and in-situ laboratory testing)

Warranty:

- 5 year limited system warranty - see www.LumenFocus.com for complete warranty terms and conditions



Ambient Operating Temp:

- 0°C to 35°C




Ordering Guide:

example: FPB v2 24 SEL5 UV FR 8SEL5

Series	Size	Output	Voltage	Shielding	CRI/CCT	Options
FPB v2			UV	FR		
FPB v2 Backlit Flat Panel Version 2 ⁽¹⁾	22 2' x 2'	SEL5 Selectable Output: 5 Field Selectable Wattage Outputs	UV 120-277	FR Frosted Acrylic Lens	8SEL5 80 CRI / 5 Field Selectable CCTs: 3000K / 3500K / 4000K / 5000K / 6500K	Blank No Options
	24 2' x 4'					
	14 1' x 4'					
	22 2' x 2'	SEL3 Selectable Output: 3 Field Selectable Wattage Outputs	UV 120-277	FR Frosted Acrylic Lens	8SEL3 80 CRI / 3 Field Selectable CCTs: 3500K / 4000K / 5000K	EM8 8W Emergency Pack ⁽²⁾
	24 2' x 4'					

Schematic:

Size	L	W	H
2' x 2'	23.74"	23.74"	1.65"
2' x 4'	47.76"	23.74"	1.65"
1' x 4'	47.76"	11.81"	1.65"




Notes

- ⁽¹⁾ All FPBv2 models sold in 2 packs only
- ⁽²⁾ 1200 lumen EM pack. Not available in 1x4. Not available in SEL5.

Mounting Accessories (order separately)

Surface Mount Kits

- SMK14 Surface Mount Kit for 1x4, white finish
- SMK22 Surface Mount Kit for 2x2, white finish
- SMK24 Surface Mount Kit for 2x4, white finish



Frame-In Kits

- FIK14 Frame-In Kit for 1x4
- FIK22 Frame-In Kit for 2x2
- FIK24 Frame-In Kit for 2x4

Suspension Cable Mount Kits

- CM2 2-Cable Kit



Performance Chart:

Catalog #	Watts	Lumens	LPW
FPB v2 22 SEL5 UV FR 8SEL5	20	2500	125
	25	3125	
	30	3750	
	35	4375	
	40	5000	
FPB v2 24 SEL5 UV FR 8SEL5	30	3750	125
	35	4375	
	40	5000	
	45	5625	
	50	6250	
FPB v2 14 SEL5 UV FR 8SEL5	20	2500	125
	25	3125	
	30	3750	
	35	4375	
	40	5000	

Catalog #	Watts	Lumens	LPW
FPB v2 22 SEL3 UV FR 8SEL3 EM8	20	2500	125
	30	3750	
	40	5000	
FPB v2 24 SEL3 UV FR 8SEL3 EM8	30	3750	125
	40	5000	
	50	6250	

Photometric Data:

Relative Luminous Intensity

