



## IES INDOOR REPORT

PHOTOMETRIC FILENAME : EWL S G2 4 LW UV FA 935.IES

### DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] LLIA002568-007A(s)

[TESTLAB] LightLab International Allentown, LLC

[ISSUE DATE] 1/3/2025

[MANUFAC] LumenFocus, LLC

[LUMCAT] EWL S G2 4 LW UV FA 935

[LUMINAIRE] Surface or pendant mounted, formed white painted steel housing,  
[MORE] formed white painted steel reflector, frosted plastic enclosure with interior

[MORE] linear prisms

[LAMPCAT] Two CL116-3500K-R90-A5 CREE G CLASS PRO 9 48UP LED boards with 48 LEDs each.

[BALLAST] One Keystone Technologies KTLD-50-UV-P1400-55-VDIM-LT1 LED driver set at 700mA

[OTHER] 120.0Vac, 60.00Hz

[OTHER] This test was performed using the absolute method of photometry.

[MORE] Lamp lumens value was set to -1

### CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	5276
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	150
Total Luminaire Watts	35.1
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.20
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.36
Basic Luminous Shape	Rectangular w/Sides
Luminous Length (0-180)	4.00 ft
Luminous Width (90-270)	0.44 ft
Luminous Height	0.12 ft

### LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	8153	7632	7845
55	7286	6862	7273
65	6267	6018	6684
75	4896	5100	6074
85	2444	4194	5579

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : EWL S G2 4 LW UV FA 935.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	602.78	N.A.	11.40
0-30	1272.22	N.A.	24.10
0-40	2068.24	N.A.	39.20
0-60	3623.27	N.A.	68.70
0-80	4609.68	N.A.	87.40
0-90	4823.77	N.A.	91.40
10-90	4667.21	N.A.	88.50
20-40	1465.46	N.A.	27.80
20-50	2281.36	N.A.	43.20
40-70	2143.78	N.A.	40.60
60-80	986.42	N.A.	18.70
70-80	397.66	N.A.	7.50
80-90	214.09	N.A.	4.10
90-110	215.48	N.A.	4.10
90-120	292.23	N.A.	5.50
90-130	352.96	N.A.	6.70
90-150	426.69	N.A.	8.10
90-180	452.23	N.A.	8.60
110-180	236.75	N.A.	4.50
0-180	5276.00	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	156.56
10-20	446.22
20-30	669.44
30-40	796.02
40-50	815.90
50-60	739.13
60-70	588.75
70-80	397.66
80-90	214.09
90-100	120.55
100-110	94.93
110-120	76.75
120-130	60.73
130-140	44.65
140-150	29.08
150-160	16.20
160-170	7.38
170-180	1.96

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : EWL S G2 4 LW UV FA 935.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	117	117	117	117	113	113	113	113	106	106	106	100	100	100	94	94	94	91
1	106	101	96	92	102	97	93	89	92	88	85	86	83	81	81	79	77	74
2	96	87	80	74	92	85	78	73	80	74	70	75	71	67	71	67	64	61
3	87	76	68	61	84	74	66	60	70	63	58	66	61	56	62	58	54	51
4	80	68	59	52	77	66	57	51	62	55	49	59	53	48	56	50	46	44
5	73	60	51	44	71	59	50	44	56	48	43	53	46	41	50	44	40	38
6	68	54	45	39	65	53	44	38	50	43	37	48	41	36	45	40	35	33
7	63	49	40	34	60	48	40	34	46	38	33	43	37	32	41	36	31	29
8	58	45	36	30	56	44	36	30	42	35	29	40	33	29	38	32	28	26
9	55	41	33	27	53	40	32	27	38	31	26	37	30	26	35	29	25	23
10	51	38	30	25	49	37	30	24	36	29	24	34	28	23	33	27	23	21

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : EWL S G2 4 LW UV FA 935.IES**

**UGR TABLE - CORRECTED**


Reflectances

Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20

Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	16.9	18.4	17.4	18.9	19.4	19.2	20.6	19.7	21.1	21.7
	3H	18.3	19.6	18.8	20.1	20.7	21.5	22.8	22.0	23.3	23.9
	4H	18.7	20.0	19.3	20.5	21.1	22.5	23.8	23.0	24.3	24.9
	6H	19.0	20.2	19.6	20.7	21.3	23.6	24.7	24.1	25.3	25.9
	8H	19.1	20.2	19.6	20.7	21.3	24.1	25.2	24.6	25.7	26.3
	12H	19.1	20.1	19.6	20.7	21.3	24.6	25.7	25.2	26.2	26.9
4H	2H	17.8	19.0	18.3	19.5	20.1	19.6	20.8	20.1	21.3	21.9
	3H	19.4	20.5	20.0	21.0	21.6	22.1	23.1	22.6	23.7	24.3
	4H	20.0	20.9	20.5	21.5	22.1	23.3	24.3	23.9	24.8	25.5
	6H	20.3	21.2	20.9	21.8	22.4	24.5	25.4	25.1	26.0	26.6
	8H	20.4	21.2	21.0	21.8	22.5	25.1	25.9	25.7	26.5	27.2
	12H	20.4	21.2	21.0	21.8	22.5	25.8	26.5	26.4	27.1	27.8
8H	4H	20.6	21.4	21.2	22.0	22.6	23.5	24.3	24.1	24.9	25.5
	6H	21.1	21.8	21.7	22.4	23.1	24.9	25.5	25.5	26.2	26.9
	8H	21.2	21.8	21.9	22.5	23.2	25.6	26.2	26.2	26.9	27.5
	12H	21.3	21.9	22.0	22.5	23.3	26.4	27.0	27.1	27.6	28.4
12H	4H	20.7	21.5	21.3	22.1	22.8	23.5	24.2	24.1	24.8	25.5
	6H	21.3	21.9	22.0	22.6	23.3	24.9	25.5	25.5	26.1	26.8
	8H	21.6	22.1	22.2	22.7	23.5	25.7	26.2	26.3	26.9	27.6

Maximum UGR = 28.4

POLAR GRAPH



Maximum Candela = 1659.652 Located At Horizontal Angle = 90, Vertical Angle = 2  
# 1 - Vertical Plane Through Horizontal Angles (90 - 270) (Through Max. Cd.)  
# 2 - Horizontal Cone Through Vertical Angle (2) (Through Max. Cd.)